

FURUTECH

Power Connectors: European and other product versions

	<p>FI-E50(R)</p> <p>12,430.-</p>	<p>High End Performance SCHUKO Connector</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Rhodium plated Conductor • Nylon/fiberglass body incorporating nano sized ceramic particles for absorption of vibration resonance. • Multi layered nonmagnetic stainless steel and carbon fiber housing and incorporating acetal copolymer. The best of damping and insulation materials for improvements in frequency extension and tonal quality.. • Specified for cable diameters from 6mm to 20mm • Dimensions: Body length 56.8mm x 40.5mm diameter x 96mm overall length • Metal cable clamp for improved grip and reduction of mechanically and electrically induced distortion 	
	<p>FI-E38(R)</p> <p>5,800.-/pcs.</p>	<p>High End Performance SCHUKO Connector</p> <ul style="list-style-type: none"> □ α (Alpha) pure-copper rhodium-plated conductors • Floating Field Damper System* • Nylon/fiberglass body incorporating carbon particles that absorb vibration and resonance • Specified for cable diameters from 6mm to 17.5mm • Dimensions: 39.6mm diameter x 90.5mm overall length • Metal cable clamp improves grip and reduces mechanically and electrically induced distortion • Rating: 16A 250V AC 	
	<p>FI-E35(R)-N1</p> <p>5,020.-</p> <p>FI-E35(G)-N1</p> <p>3,920.-</p>	<p>High End Performance SCHUKO Connector</p> <p>α (Alpha) pure-copper rhodium-plated conductors</p> <ul style="list-style-type: none"> • Floating Field Damper System* • Nylon/fiberglass body incorporating carbon particles that absorb vibration and resonance • Specified for cable diameters from 6mm to 17.5mm • Dimensions: 39.6mm diameter x 90.5mm overall length • Metal cable clamp improves grip and reduces mechanically and electrically induced distortion • Rating: 16A 250V AC 	
	<p>FI-E11(G)</p> <p>2,510.-</p> <p>FI-E11(Cu)</p> <p>1,880.-</p>	<p>High Performance SCHUKO Connector</p> <p>α (Alpha) pure-copper rhodium-plated conductors</p> <ul style="list-style-type: none"> • Floating Field Damper System* • Nylon/fiberglass body incorporating carbon particles that absorb vibration and resonance • Specified for cable diameters from 6mm to 17.5mm • Dimensions: 39.6mm diameter x 90.5mm overall length • Metal cable clamp improves grip and reduces mechanically and electrically induced distortion • Rating: 16A 250V AC 	

	<p>FI-E30(R) 1,880.-</p> <p>FI-E30(G) 1,255.-</p>	<p>High Performance SCHUKO sockets</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic copper alloy Conductor • Materials: Nylon/fiberglass body • Specifications: Accommodates wire diameters to 2.5mm max.(12 AWG) • Dimensions: 50.6 (L) x 50.6 (W) x 36mm (H) • Rated: 16A/250V 	
	<p>FI-AU(R) 5,020.-</p> <p>FI-AU(G) 4,080.-</p>	<p>High End Performance AS/NZS Connector</p> <ul style="list-style-type: none"> • Pure copper α (Alpha) Conductor • Earth (Ground) Jumper System. • Material: Nylon/fiberglass front body • Polycarbonate shell • Specifications: Accommodates cable diameters of 6.6mm to 20.0mm • Dimensions: Body length 40.0mm x 44mm diameter x 80mm overall length • Rated: 10A/250V 	
	<p>FI-UK(R) (1363) 6,150.-</p> <p>FI-UK(G) (1363) 5,020.-</p>	<p>High End Performance BS-1363 Connector</p> <ul style="list-style-type: none"> • Eutectic copper alloy α (Alpha) Conductor • Material: Fireproof ABS body/housing • Specifications: Accommodates cable diameters of 6.0mm to 20.0mm • Dimensions: Body 48mm (W) x 50.2mm (L) x 55.8mm (H) • Rated: 13A Fused/250V 	
	<p>FT-SWS (R) 5,520.-</p> <p>FT-SWS (G) 4,700.-</p> <p>FP-SWS (G) 3,450.-</p>	<p>FT-SWS (R) Rhodium Plated Non-magnetic pure copper conductors and Carbon fiber finished front plate</p> <ul style="list-style-type: none"> • α (Alpha) Pure Copper main Conductor (t : 0.5mm) • Material: Nylon/fiberglass body and Poly carbonate cover • 1.0mm thick Bracket with a Zinc/steel brace plate • Carbon fiber finished Cast Zn-Mg Alloy Front Plate • Specified for wire diameters of 2.8mm or 5.5 Sq.mm/10AWG Max. (set screw) • Dimensions: 95.0mm (L) x 95.0mm (W) x 48.0mm(H) • Furutech's total attention to detail and build quality extends right down to a specially designed patent-pending pressure plate that increases the contact area of the Alpha Conductors 	