





FURUTECH

Audio Accessories RCA

	<p>CF-102(R) (2 pcs.-/Set)</p> <p>7,325.-</p>	<p>Carbon Fiber Series RCA Connector</p> <ul style="list-style-type: none"> • α (Alpha) OCC rhodium-plated center conductor • α (Alpha) copper alloy rhodium-plated body • Carbon fiber and nonmagnetic stainless steel housing • Copper alloy connector body • Copper alloy set screw • Specified for cable diameters max. 9.3mm • Dimensions: 14.0mm diameter x 54.0mm overall length 	
	<p>FP-108(R)</p> <p>7,370.-/Set</p> <p>1,842.-/pcs</p>	<p>High End Performance RCA Connector</p> <ul style="list-style-type: none"> • α (Alpha) OCC rhodium-plated center conductor • Copper alloy rhodium-plated body • Copper alloy black-painted locking housing • Teflon insulation • Connections: Set screw • Specified for cable diameters up to 9.3mm max. • Dimensions: • 13.8mm ± 0.1mm diameter x 54mm ± 0.1mm overall length 	
	<p>FP-120F(R)</p> <p>7,030.-/Set</p> <p>1,757.-/pcs</p>	<p>High End Performance RCA connector (Filament central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • Phosphor bronze α (Alpha) Filament center pin • Copper alloy body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 12.3mm • Dimensions: 13.8mm ± 0.1 diameter x 61.2mm ± 0.1mm overall length 	
	<p>FP-106(R)</p> <p>6,900.-/Set</p> <p>1,725.-/pcs</p>	<p>High End Performance RCA connector (Filament central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • Phosphor bronze α (Alpha) Filament center pin • Copper alloy body and locking collet • Teflon insulation • Connections: Set screw • Specified for cable diameters up to 9.3mm • Dimensions: 13.8mm ± 0.1 diameter x 54mm ± 0.1mm overall length 	
	<p>FP-101(G)</p> <p>5,960.-/Set</p> <p>1,490.-/pcs</p>	<p>High End Performance RCA connector (Filament central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • Phosphor bronze α (Alpha) Filament center pin • Copper alloy body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 9.3mm • Dimensions: 13.8mm ± 0.1 diameter x 54mm ± 0.1mm overall length 	
	<p>FP-101(G)</p> <p>5,335.-/Set</p>	<p>High Performance Audio RCA Connectors (PCOCC central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • α (Alpha) OCC Conductor center pin • Copper alloy body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 9.3mm • Dimensions: 13.8mm ± 0.1 diameter x 54.4mm overall length 	

	<p>FP-160(G) 3,765.-/Set 895.-/pcs.</p>	<p>High Performance Audio RCA Connectors (Eutectic cast copper alloy central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • Eutectic cast copper alloy α (Alpha) center pin • Copper alloy body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 9.3mm • Dimensions: 14.8mm \pm 0.1 diameter x 52.1mm \pm 0.1mm overall length 	
	<p>FP-126(R) 3,660.-/Set 915.-/pcs.</p> <p>FP-126(G) 2,300.-/Set 565.-/pcs.</p>	<p>High Performance Audio RCA Connectors (PCOCC central pin)</p> <ul style="list-style-type: none"> • α (Alpha) OCC Conductor center pin • Copper alloy body and Teflon insulation • Connections: Soldered • Specified for cable diameters up to 7.3mm • Dimensions: 12.6mm \pm 0.1 diameter x 39.3mm overall length 	
	<p>FP-104(G) 3,765.-/Set 895.-/pcs.</p>	<p>High Performance Audio RCA Connectors (Eutectic cast brass central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • Eutectic cast brass α (Alpha) center pin • Brass body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 8.3mm • Dimensions: 13mm \pm 0.1 diameter x 5.5mm \pm 0.1mm overall length 	
	<p>FP-162(G) 250.-/pcs.</p>	<p>High Performance Audio RCA Connectors (Eutectic cast copper alloy central pin)</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast copper alloy center pin • Copper alloy body and Teflon insulation • Connections: Soldered • Specified for cable diameters up to 7.3mm • Dimensions: 11.9mm \pm 0.1 diameter x 37.3mm overall length 	
	<p>FP-3-117(R) 2,135.-/set 1,020.-/pcs.</p>	<p>High Performance Audio BNC Connector</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast copper alloy center pin • Rhodium-plated copper alloy body with Teflon insulation • Connections: Soldered • Specified for cable diameters up to 8mm • Dimensions: 14mm \pm 0.1 diameter x 43mm \pm 0.1mm overall length 	

	<p>FP-DIN(L) 5,490.-</p> <p>FP-DIN 4,620.-</p>	<p>FP-DIN Straight and FP-DIN (L) Phono Connector Series</p> <ul style="list-style-type: none"> • Rhodium-plated α (Alpha) phosphor bronze conductor • Teflon Insulated Body • Nonmagnetic stainless steel housing • Soldered connections • Specified for cable diameters max. 10.0mm • Dimensions: FP-DIN • 14.0mm diameter x 54.0mm overall length • FP-DIN(L) • 45(L) X 19(W) X 33.4(H) mm approx. 	 
	<p>FP-601M(R) 3,845.-</p> <p>FP-601M(G) 3,140.-</p>	<p>High End Performance XLR Connectors</p> <ul style="list-style-type: none"> • Beryllium copper and phosphor bronze α (Alpha) Conductor • Copper alloy body and PVDF Teflon insulation • Connections: Soldered • Specified for cable diameters up to 12mm • Dimensions: 19.5mm \pm 0.1 diameter x 48.5mm \pm 0.1mm overall length 	
	<p>FP-602F(R) 4,550.-</p> <p>FP-602F(G) 3,530.-</p>	<p>High End Performance XLR Connectors</p> <ul style="list-style-type: none"> • Beryllium copper and phosphor bronze α (Alpha) Conductor • Copper alloy body with PVDF Teflon insulation • Connections: Soldered • Specified for cable diameters up to 12mm • Dimensions: 19.5mm \pm 0.1 diameter x 48.5mm \pm 0.1mm overall length 	
	<p>FP-701M(G) 628.-</p> <p>FP-702F(G) 705.-</p>	<p>High Performance XLR Connectors</p> <ul style="list-style-type: none"> • Eutectic cast copper alloy α (Alpha) center pin • Copper alloy body and PBT plus fiberglass insulation • Connections: Soldered • Specified for cable diameters up to 9mm • Dimensions: 21.3mm \pm 0.1 diameter x 63.2mm \pm 0.1mm overall length 	

	<p>FP- 681M(R) FP- 682F(R)</p> <p>2,825.-/pcs.</p> <p>FP- 681M(G) FP- 682F(G)</p> <p>1,880.-/pcs.</p>	<p>High End Performance XLR Sockets</p> <ul style="list-style-type: none"> •Beryllium copper and phosphor bronze α (Alpha) Conductor •Copper alloy body and PVDF Teflon insulation •Zn-Mg Alloy Casting Housing •Connections: Soldered •FP-681M: Housing---36.5\pm 0.1mm diameter X21.2mm\pm 0.1mm,33.7mm\pm 0.1mm overall length •FP-682F: Housing---36.5\pm 0.1mm diameter X30.2mm \pm 0.1mm,39.3mm \pm 0.1mm overall length 	
	<p>FP- 781M(G)</p> <p>565.-</p> <p>FP- 782F(G)</p> <p>625.-</p>	<p>High Performance XLR Sockets</p> <ul style="list-style-type: none"> •α (Alpha) Eutectic cast copper alloy center pin •Copper alloy body with PBT and fiberglass insulation •Connections: Soldered •Zn-Mg Alloy Casting Housing <p>Dimensions:</p> <ul style="list-style-type: none"> • FP-781M: Housing---36.6\pm 0.1mm X22.3mm\pm 0.1mm,27.5mm\pm 0.1mm overall length •FP-782F: Housing---36.6\pm 0.1mm X27.1mm\pm 0.1mm,43.9mm\pm 0.1mm overall length 	
	<p>FP- 703(G) (Mono)</p> <p>625.-</p> <p>FP- 704(G) (Stereo)</p> <p>750.-</p>	<p>High Performance Phone Jacks</p> <ul style="list-style-type: none"> •α (Alpha) Eutectic cast copper alloy center pin •Copper alloy rear housing with PBT and fiberglass insulation •Specified for cable diameters up to 8mm •Connections: Soldered •Zn-Mg Alloy Casting body housing <p>Dimensions:</p> <ul style="list-style-type: none"> •FP-703: Housing---17.8\pm 0.1mm diameter X65.8mm\pm 0.1mm,97.3mm\pm 0.1mm overall length •FP-704: Housing---17.8\pm 0.1mm diameter X65.8mm\pm 0.1mm,97.8mm\pm 0.1mm overall length 	