













FURUTECH

Audio Spade and Banana

	<p>CF-201(R) 2 pcs./set</p> <p>7,325.-</p>	<p>CF-201(R) Pure Transmission Spade Connector</p> <ul style="list-style-type: none"> • α (Alpha) pure-copper rhodium-plated center conductor • α (Alpha) nonmagnetic stainless steel body • Carbon fiber and nonmagnetic stainless steel housing • Conductors fixed by set screw or solder • Specially designed copper alloy set screw ensures stability • Specified for wire diameters max. 5.5mm • Dimensions: 15.2mm diameter x 70.0mm overall length 	
	<p>CF-202(R) 2 pcs./set</p> <p>9,770.-</p>	<p>Carbon Fiber Series Banana Connector CF-202(R)</p> <ul style="list-style-type: none"> • α (Alpha) pure-copper rhodium-plated center conductor • α (Alpha) nonmagnetic stainless steel body • Beautifully finished highly damped carbon fiber and nonmagnetic stainless steel housing • Conductor wire fixed with set screw or solder • Specially designed wire compression clamp enhances stability and contact area • Strain relief/resonance dampening ring • Locking compression collar for small diameter wire • Specified for wire diameters to max. 5.5mm • Dimensions: 15.2mm diameter x 64.2mm overall length 	
	<p>FP-218(R)</p> <p>3,410.-/set 815.-/pcs.</p> <p>FP-218(G)</p> <p>2,800.-/set 660.-/pcs.</p>	<p>High Performance Spade Connector</p> <ul style="list-style-type: none"> • α (Alpha) pure-copper 24k Gold-plated or Rhodium-plated conductors • Connections: Terminal press or Soldered • Special two stage fixed wire crimp construction to ensure contact stability. Inner crimp for raw conductor and outer crimp for unstripped wire. • Specified for wire diameters of up to 6mm max. • Dimensions: Space between conductor 8.1mm/13.0mm(W) x 35.5mm overall length Crimp barrel: 8.0mm Outer diameter x 15.0mm (L) 	 
	<p>FP-201(R)</p> <p>3,765.-</p>	<p>High Performance Audio Spade Terminals)</p> <ul style="list-style-type: none"> • Pure copper α (Alpha) Conductors • Connections: Set screw or soldered • Specified for cable diameters up to 6mm • Dimensions: Space between Conductor: 8.2mm o 12.9mm ± 0.1 (W) x 40mm ± 0.1mm overall length 	
	<p>FP-201(G)</p> <p>2,825.-</p>	<p>High Performance Audio Spade Terminals)</p> <ul style="list-style-type: none"> • Pure copper α (Alpha) Conductors • Connections: Set screw or solder • Specified for cable diameters up to 6mm • Dimensions: Space between Conductor: 8.2mm o 12.9mm ± 0.1 (W) x 40mm ± 0.1mm overall length 	

	<p>FP-202(R)</p> <p>4,390.-/set 1,035.-/pcs.</p>	<p>High Performance Audio Banana Connectors</p> <ul style="list-style-type: none"> • Eutectic cast copper alloy α (Alpha) pins • Connections: Set-screw • Specified for cable diameters up to 7mm • Dimensions: Space between Conductor: 8.2mm o 12mm diameter x 26.7mm \pm 0.1mm (H) x 46mm overall length 	
	<p>FP-202(G)</p> <p>3,640.-/set 860.-/pcs.</p>	<p>High Performance Audio Banana Connectors</p> <ul style="list-style-type: none"> • Eutectic cast copper alloy α (Alpha) pins • Connections: Set-screw • Specified for cable diameters up to 7mm • Dimensions: Space between Conductor: 8.2mm o 12mm diameter x 26.7mm \pm 0.1mm (H) x 46mm overall length 	
	<p>FP-203(R)</p> <p>2,070.-/set 485.-/pcs.</p>	<p>High Performance Audio Spade Terminals</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductors • Connections : Soldered or Press • Specified for cable diameters up to 4mm • Dimensions: Space between Conductor: 8.2mm o 12.9mm \pm 0.1 (W) x 24mm \pm 0.1mm overall length 	
	<p>FP-203(G)</p> <p>1760.-/set 410.-/pcs.</p>	<p>High Performance Audio Spade Terminals</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductors • Connections : Soldered or Press • Specified for cable diameters up to 4mm • Dimensions: Space between Conductor: 8.2mm o 12.9mm \pm 0.1 (W) x 24mm \pm 0.1mm overall length 	
	<p>FP-200B(R)</p> <p>3,765.-/set</p> <p>FP-200B(G)</p> <p>485.-</p>	<p>High Performance Audio Banana Connectors</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor Bronze pin • Connections: Set-screw or Soldered * Contact pin specially designed to increase contact area and effect stable more transmission. * Unique main body design that ensures very firm wire connections that can be fixed by set screw or soldered. * Treated with FURUTECH α(Alpha) Process to minimize transmission loss * Material: Banana Conductor—Phosphor Bronze Plate / Housing—Copper alloy * Specifications: Max. Wire diameters up to ϕ5.0mm * Dimensions: Housing---ϕ11.1mm X 30.3 mm L, Banana Conductor---ϕ4.6mm X 19.7 mm L, Overall length : 50 mm 	 
	<p>FP-209-10(G) (20pcs./set)</p> <p>2,890-/set 145.-/pcs.</p>	<p>High Performance RCA connector series FP-209-10(G)</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductors • Connections: solder or crimp • Specified for wire diameters up to 4mm (8AWG) • Dimensions: 8mm \pm 0.1mm (W) x 25mm \pm 0.1mm overall length • Perfect for use with Furutech wall receptacle connections and Furutech AC / IEC power connections 	