

FURUTECH

INLET

	<p>FI-33(R) 5,020.-/pcs.</p> <p>FI-33(G) 4,080.-/pcs.</p>	<p>High End Performance 20A IEC Inlet</p> <ul style="list-style-type: none"> • Pure copper α (Alpha) Conductor • Material: Nylon/fiberglass • Specified for wire diameters of 4mm (set screw) • Dimensions: 60.4mm (W) x 30.4mm (D) x 38.7mm (H) • Rated: 20A/125V and 16A/250V 	
	<p>FI-09(R) 4,390.-/pcs.</p> <p>FI-09(G) 3,450.-/pcs.</p>	<p>High End Performance IEC Inlet</p> <p>Pure copper α (Alpha) Conductor</p> <ul style="list-style-type: none"> •Materials: Nylon/fiberglass •Specifications: Accommodates wire diameters to 4mm (set-screw) •Dimensions: 60 (W) x 30mm (D) x 36.2mm (H) •Body length 40.0mm x 44mm diameter x 80mm overall length •Rated: 15A/250V 	 <p>FI-09 (R)</p>
	<p>FI-10(R) 1,440.-/pcs.</p> <p>FI-10(G) 1,100.-/pcs.</p>	<p>High Performance IEC Inlet</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic (low temperature) cast Copper alloyConductor • Nylon and fiberglass housing • Specifications: Accommodates wire diameters to 3.2mm • Connection: Set screw • Dimensions: 50.9mm (W) x 24.1mm (D) x 28.8 (H) • Rated: 15A/250V 	
	<p>FI-03(R) 1,200.-/pcs.</p> <p>FI-03(G) 935.-/pcs.</p>	<p>High Performance IEC Inlet</p> <ul style="list-style-type: none"> • α (Alpha) copper alloy conductor • PBT and fiberglass housing • Dimensions: 44.0mm (W) x 28.6mm (D) x 33.0mm (H) • Rating: 10A/250V • Standard : IEC 320-1 C14 • Approvals : UL/CSA/VDE/DEMKO/SEMKO/NEMKO/FIMKO 	
	<p>AC-INLET (R) 690.-/pcs.</p> <p>AC-INLET(G) 500.-/pcs.</p>	<p>High Performance IEC Inlet</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic (low temperature) cast copper alloy Conductor • PBT and fiberglass housing • Connections: Soldered • Dimensions: 50.9mm (W) x 24.1mm (D) x 28.8 (H) • Rated: 15A/125V 10A/250V 	