

# FURUTECH

## Receptacles

	<p><b>FP-15A(Cu)-N1</b></p> <p><b>2,825.-</b></p>	<p><b>High Performance Pure Culprum-plated Duplex Receptacle</b></p> <p>Non-magnetic Pure Cuprum plated Phosphor Bronze conductor ( t: 0.8 mm )</p> <p>Accommodates cable diameters from 10 AWG to 24 AWG. Dimensions: 104.2mm×33.5mm (L×W), 28.2mm thick.</p> <p>Materials: Main body - Nylon and Glass Fiber</p> <p>Cover - Polycarbonate White for FP-15A-N1(G)and Black for FP-15A-N1(Cu)</p> <p>Connections: Set-screw c(UL) Approved</p>	
	<p><b>FP-15A(G)-N1</b></p> <p><b>3,695.-</b></p>	<p><b>High Performance 24k Gold-plated Duplex Receptacle</b></p> <p>Non-magnetic 24k Gold plated plated Phosphor Bronze conductor ( t: 0.8 mm )</p> <p>Accommodates cable diameters from 10 AWG to 24 AWG. Dimensions: 104.2mm×33.5mm (L×W), 28.2mm thick.</p> <p>Materials: Main body - Nylon and Glass Fiber</p> <p>Cover - Polycarbonate White for FP-15A-N1(G)and Black for FP-15A-N1(Cu)</p> <p>Connections: Set-screw c(UL) Approved</p>	
	<p><b>FP-15A(R)-N1</b></p> <p><b>4,730.-</b></p>	<p><b>High Performance Rhodium-plated Duplex Receptacle</b></p> <p>Non-magnetic Rhodium plated plated Phosphor Bronze conductor ( t: 0.8 mm )</p> <p>Accommodates cable diameters from 10 AWG to 24 AWG. Dimensions: 104.2mm×33.5mm (L×W), 28.2mm thick.</p> <p>Materials: Main body - Nylon and Glass Fiber</p> <p>Cover - Polycarbonate White</p> <p>Connections: Set-screw c(UL) Approved</p>	
	<p><b>FT-D20A(G)</b></p> <p><b>6,200.-</b></p>	<p><b>High End Performance 20A125V Duplex Receptacle</b></p> <ul style="list-style-type: none"> <li>• Gold-plated α (Alpha) Phosphor Bronze Conductor(t : 0.8mm)</li> <li>• Material: Nylon/fiberglass body and polycarbonate cover; parts fixed with a 2.0mm thick Stainless brace plate</li> <li>• Specified for wire diameters of 4mm (set screw)</li> <li>• Dimensions: 104.0mm(L) x 47.2mm(W) x 28.0mm(H)</li> </ul> <p>c(UL) Approved</p>	
	<p><b>FT-D20A(R)</b></p> <p><b>8,285.-</b></p>	<p><b>High End Performance 20A125V Duplex Receptacle</b></p> <ul style="list-style-type: none"> <li>• Rhodium-plated α (Alpha) Phosphor Bronze Conductor(t : 0.8mm)</li> <li>• Material: Nylon/fiberglass body and polycarbonate cover; parts fixed with a 2.0mm thick Stainless brace plate</li> <li>• Specified for wire diameters of 4mm (set screw)</li> <li>• Dimensions: 104.0mm(L) x 47.2mm(W) x 28.0mm(H)</li> </ul> <p>c(UL) Approved</p>	

	<p><b>FT-S20A(G)</b></p> <p><b>5,585.-</b></p>	<p><b>High End Performance 20A125V Single Receptacle</b></p> <ul style="list-style-type: none"> <li>• Gold-plated α (Alpha) Phosphor Bronze Conductor(t : 0.8mm)</li> <li>• Material: Nylon/fiberglass body and Poly carbonate cover; parts fixed with a 2.0mm thick stainless brace plate</li> <li>• Specified for wire diameters of 4mm (set screw)</li> <li>• Dimensions: 104.0mm(L) x 47.2mm(W) x 28.0mm(H)</li> </ul> <p>c(UL) Approved</p>	
	<p><b>FT-S20A(R)</b></p> <p><b>6,590.-</b></p>	<p><b>High End Performance 20A125V Single Receptacle</b></p> <ul style="list-style-type: none"> <li>• Rhodium-plated α (Alpha) Phosphor Bronze Conductor(t : 0.8mm)</li> <li>• Material: Nylon/fiberglass body and Poly carbonate cover; parts fixed with a 2.0mm thick stainless brace plate</li> <li>• Specified for wire diameters of 4mm (set screw)</li> <li>• Dimensions: 104.0mm(L) x 47.2mm(W) x 28.0mm(H)</li> </ul> <p>c(UL) Approved</p>	
	<p><b>Outlet cover 103-D</b></p> <p><b>4,265.-</b></p>	<p><b>High End Performance Sonorous Series 103-D Duplex Outlet Cover Plates</b></p> <p>103 series: Stainless Fixed Screw/Size : # M4 X 12mm(L) Carbon fiber and Grass fiber finished Stainless Steel cover Cover Size : 71X116 mm(t : 2.3mm ± 0.1mm) Receptacle and cover sold separately.</p>	
	<p><b>Outlet cover 102-D</b></p> <p><b>1,440.-</b></p>	<p><b>New and greatly improved Pure Transmission 102-D Duplex Receptacle Cover Plate</b></p> <p>102 series: Stainless Fixed Screw/Size : M4 X 12mm(L) Stainless Cover /Size : 71X116 mm(t : 1.2mm) With "FO-Q" vibration damping material c(UL) Approved</p>	
	<p><b>Outlet cover 102-S</b></p> <p><b>1,440.-</b></p>	<p><b>New and greatly improved Pure Transmission 102-S single Receptacle Cover Plate</b></p> <p>102 series: Stainless Fixed Screw/Size : M4 X 12mm(L) Stainless Cover /Size : 71X116 mm(t : 1.2mm) With "FO-Q" vibration damping material Receptacle and cover sold separately</p>	
	<p><b>Outlet cover 102-2D</b></p> <p><b>2,680.-</b></p>		