




FURUTECH

HDMI Cable and Phono Cable

	<p>HDMI – xv 1.3b</p> <p>1 M (15,950.-) 2 M (20,000.-) 3 M (23,980.-) 5 M (31,900.-) 8 M (41,580.-) 10 M (47,960.-) 12 M (54,340.-) 15 M (63,910.-) 20 M (79,860.-)</p>	<p>HDMI Digital Cable – xv1.3 (High-Definition Multimedia Interface Cable)</p> <p>Successfully completed ATC Compliance testing at the HDMIλ Authorized Testing Center---Silicon Image (1080P / 1.3b Ver. Cat.2 / 10.2 Gbps / 16 bit / 60Hz max.). (1080P /1.3b ver. / Cat.2 / 13.4 Gbps / 12 bit /120Hz max.) 1m, 2m, 3m, 5m only</p> <p>Main Conductor: α(Alpha) conductor (24 AWG Silverλ plated μ–OFC solid core wire) for ultra low transmission loss.</p> <p>HDMIλ Connector constructed of Pearl Chrome finished Aluminum Alloy with non-magnetic 24K Gold Plated α (Alpha) contacts</p> <p>Cable: UL Specified Pb freeλ Fire-retardant PVC Sheath and 5 layer shielding around conductors for superior noise isolation.</p> <p>Production Lengths:λ 1M/2M/3M/5M/8M/10M/12M/15M/20M.</p> <p>α(Alpha) conductor : Silver plated μ–OFC conductor wire strands treated with the α(Alpha) process.</p>	
	<p>HDMI – N1 (1.3 ver./1080p)</p> <p>1.2 M (7,590.-) 2.5 M (11,990.-) 5.0 M (20,240.-) 8.0 M (26,290.-) 10 M (31,680.-) 12 M (37,180.-) 15 M (44,990.-) 20 M (58,300.-)</p>	<p>High-Definition Multimedia Interface Cable for Audio & Visual Equipment HDMI-N1 Digital Cable (1.3 ver./1080p) Category 2</p> <p>The FURUTECH HDMI Cable has successfully completed ATC Compliance testing at the HDMI Authorized Testing Center---Silicon Image.</p> <p>Main conductor wire: α (Alpha) Silver plated μ–OFC conductor for minimal transmission loss.</p> <p>HDMI Connector: α (Alpha) non-magnetic 24k Gold-plated conductor with 24K Gold-plated non-magnetic Bronze Body.</p> <p>Sheath: Flexible PVC (Violet).</p> <p>Superior noise isolation 3 Layered Shielding.</p> <p>Production Lengths:1.2m 2.5m 5m 8m 10m 12m 15m 20m</p> <p>A (Alpha) conductor is the fine μ–OFC conductor wire strands treated with the α (Alpha) process.</p>	
	<p>HDMI – H1 (1.3 ver./1080p)</p> <p>1.2 M (3,465.-) 2.5 M (6,240.-) 5.0 M (10,395.-)</p>		
	<p>F-1 Adaptor</p> <p>2,195.-</p>	<p>HDMI female to DVI-D mail Adaptor</p> <p>Gold Plated α(Alpha)conductor</p>	

	<p>AG-12 L-DIN</p> <p>27,170.-</p> <p>AG-12 DIN</p> <p>24,530.-</p>	<p>Ag-12 Pure Transmission Silver-Plated Phono Cable • DIN/RCA and Right angled DIN/RCA Ag-12-L(L-Din/RCA)</p> <ul style="list-style-type: none"> • α (Alpha) silver-plated μ-OFC Conductor • 4-layer shield construction for improved noise insulation • Main Insulation: Air-foamed polyethylene • Connectors <ul style="list-style-type: none"> o Furutech-engineered rhodium-plated DIN or L-DIN and FP-126(R) Alpha-OCC RCA connectors • The best damping and insulation materials for improved frequency extension and tonal balance • Carefully engineered cable clamp improves grip and reduces mechanical and electrically-induced distortion • Dimensions: Cable diameter ~9.5mm • Overall length: 1.2M/set 	
	<p>AG-12-R4</p> <p>24,530.-</p>	<p>Ag-12-R4 Pure Transmission Phono RCA Cable</p> <ul style="list-style-type: none"> • α (Alpha) silver-plated μ-OFC Conductor o Fine OFC wire strands treated with Furutech's Alpha Cryogenic and Demagnetizing process • Three-layer shielding for improved noise insulation • Main Insulation/dielectric o Air-foamed polyethylene • Connectors o Furutech-engineered rhodium-plated FP-126(R) Alpha-OCC RCA connectors • Carefully designed cable clamp improves grip and reduces mechanical and electrically-induced distortion • Finest damping and insulation materials for improved frequency extension and tonal balance • Dimensions: Cable diameter ~9.5mm • Overall length: 1.2m/set 	
	<p>GT2 USB</p> <p>GT2 0.6 m. 4,500.-</p> <p>GT2 1.2 m. 5,500.-</p> <p>GT2 1.8 m. 6,300.-</p> <p>GT2 3.6 m. 8,800.-</p> <p>GT2 5.0 m. 10,800.-</p> <p>GT2 7.0 m. 13,700.-</p> <p>GT2 10 m. 18,000.-</p>	<p>Furutech GT2 USB 2.0 Cables</p> <p>Features</p> <ul style="list-style-type: none"> • Main conductor: Silver-plated α (Alpha) OCC Conductors • Main Insulation: Special-grade high-density polyethylene • 3-layer shield construction for improved noise insulation • Connectors: Furutech-engineered 24k gold-plated USB series Connectors • The best damping and insulation materials for improved frequency extension and tonal balance • Cable Types <ul style="list-style-type: none"> o GT2 USB-A (Type A-A) / USB-B (Type A-B) / USB-mini B (Type A-mini B) • Cable Lengths <ul style="list-style-type: none"> o 0.6m (2ft) / 1.2m (4ft) / 1.8M (6ft) / 3.6m (12ft) / 5.0m (16.5ft) o 7.0m (23ft) and 10.0m (33ft) by request 	

