




# FURUTECH

## High End Performance Flux Series

	<p><b>Powerflux Power Cord</b></p> <p><b>112,970.-/pcs.</b></p>	<ul style="list-style-type: none"> <li>• Fitted with Furutech's top-of-the-line FI-50 Piezo Ceramic series connectors</li> <li>• Furutech's beautifully-finished FI-50(R) IEC and FI-50M(R) Piezo Ceramic series connector housings are made of layers of carbon fiber in a damping and insulating acetal copolymer surrounded by nonmagnetic stainless steel. Europe version features FI-E50(R) Schuko Connector</li> <li>• The connector bodies combine two "active" materials: Nano-sized ceramic particles and powdered carbon. Nylon and fiberglass are incorporated as well forming an extremely effective, mechanically and electrically nonresonant connector body that may just be the most sophisticated in the world.</li> <li>• Piezo Ceramic series connectors feature <math>\alpha</math> (Alpha) Pure Copper conductors equipped with Furutech's advanced Earth/Ground Jumper System (US Patent No.: 6,669,491)</li> <li>• Patent-pending metal cable clamps improves grip and reduces mechanically- and electrically-induced distortion -- also features patent-pending specially-engineered pressure plates</li> <li>• Cable features a full <math>\alpha</math> (Alpha) conductor shield to protect the signal from radiated noise</li> <li>• RoHS-compliant flexible PVC sheaths enhances vibration control</li> <li>• Special high-grade PE insulation/dielectric reduces capacitance</li> </ul>	
	<p><b>Lineflux (RCA)</b></p> <p><b>86,300.-/set</b></p>	<p><b>Lineflux Cables</b></p> <ul style="list-style-type: none"> <li>• Solid <math>\alpha</math> (Alpha) OCC Conductor</li> <li>• Double-layer shielding for improved noise insulation</li> <li>• Insulation/Dielectric: High-grade polyethylene</li> <li>• Connectors: <ul style="list-style-type: none"> <li>o Beautiful, hefty rhodium-plated carbon fiber and stainless steel</li> <li>o CF-102R RCA's connectors</li> </ul> </li> <li>• The best damping and insulation materials available for improved frequency extension and smooth tonal balance</li> <li>• Carefully engineered cable clamp improves grip reduces mechanical and electrically-induced distortion</li> <li>• Dimensions: Cable diameter approx. 13.0mm • Overall length: 1.2M/set</li> </ul>	
	<p><b>Lineflux (XLR)</b></p> <p><b>97,970.-/set</b></p>	<p><b>Lineflux Cables</b></p> <ul style="list-style-type: none"> <li>• Solid <math>\alpha</math> (Alpha) OCC Conductor</li> <li>• Double-layer shielding for improved noise insulation</li> <li>• Insulation/Dielectric: High-grade polyethylene</li> <li>• Connectors: <ul style="list-style-type: none"> <li>o Beautiful, hefty rhodium-plated carbon fiber and stainless steel</li> <li>o CF-601MR / CF602FR XLR connectors</li> </ul> </li> <li>• The best damping and insulation materials available for improved frequency extension and smooth tonal balance</li> <li>• Carefully engineered cable clamp improves grip reduces mechanical and electrically-induced distortion</li> <li>• Dimensions: Cable diameter approx. 13.0mm • Overall length:</li> </ul>	

# FURUTECH

## High End Performance Flux Series

### Jumperflux-B

18,430.-/set

### Jumperflux-S

18,430.-/set

### Speakerflux Jumper Cables

- 7 bundles x 68-strand  $\alpha$  (Alpha) OCC conductor 0.127mm, 3.6mm total diameter
- Insulation: High-grade PE 5.3mm diameter
- Jacket: RoHS-compliant nylon braid approx. 6.2mm
- Connectors: Jumperflux-S with FP-201R spade terminals and Jumperflux-B with FP-200BR banana connectors



### Speakerflux Cables

137,250.-/set

### Speakerflux Cables (3.0m x2)

- $\alpha$  (Alpha) OCC Pure Transmission Conductors
- Beautifully-engineered high-performance rhodium-plated nonmagnetic pure copper spades Type CF-201R
- Nonmagnetic rhodium-plated banana connectors Type CF-202R
- Dielectric/insulation: High grade PE reduces capacitance for improved vibration damping
- Results in greater resolution, clarity, powerful dynamics, and an ultra-quiet soundstage in which music develops more fully without artificial upper-frequency "presence region" glare



# FURUTECH

## High End Performance Flux Series

**Silver Arrows-12-R4**

**80,500.-**

**Silver Arrows-12**

**77,600.-**

**Silver Arrows-12-L**

**77,600.-**

### Silver Arrows Phono Cable Features

- $\alpha$  (Alpha) Pure Silver Conductors
- Three-layer shielding for improved noise insulation
- Four-way grounding and external ground wire
- Insulation/Dielectric: Special-grade air-foamed polyethylene
- Connectors: Furutech-engineered rhodium-plated Carbon and Stainless finished CF-DIN connector or L-DIN connector and CF-102(R)  $\alpha$  (Alpha) OCC RCA connectors
- Carefully engineered cable clamp improves grip and reduces mechanical and electrically-induced distortion
- Dimensions: Cable diameter approx. 10.8mm • Overall length: 1.2M/set



**Flux-50 Filter**

**36,860.-**

### The Furutech Flux-50 Inline Power Filter

- Fitted with Furutech's top-of-the-line high end performance Piezo Ceramic body rhodium plated  $\alpha$  (Alpha) non-magnetic pure copper conductors FI-50R Connectors
- GC-303+EMI Filter AC-1501R Rhodium plated  $\alpha$  (Alpha) non-magnetic copper alloy conductors
- Earth/Ground Jumper System (US Patent No.: 6,669,491 )
- Patent pending metal cable clamp improves grip and reduces mechanically and electrically induced distortion plus patent-pending specially engineered pressure plate
- Cable features an  $\alpha$  (Alpha) conductor shield to protect against radiated noise.
- RoHS compliant flexible PVC sheath improves vibration isolation
- Special high-grade PE Insulation contributes to a reduction in capacitance.
- Dimensions: Outer Diameter 50.7mm max., Overall Length 30cm Approx.

