

FURUTECH

RCA & XLR

<p>CF-102 NCF (2 pcs./Set) 13,250.-</p>	<p>Furutech introduces the CF-102 NCF top-of-the-line RCA connector</p> <ul style="list-style-type: none"> • α (Alpha) OCC Rhodium-plated one-piece construction conductor pin injected with Furutech's ultimate anti-static and resonance damping material - NCF NCF delivers improvements in the depth and focus of the sound stage, harmonics and tonal balance. Low frequencies are cleaner, with a greater sense of definition made possible by a lowered noise floor • α (Alpha) Copper Alloy Rhodium-plated Body • Nonmagnetic stainless steel and silver-plated carbon fiber housing. The best of damping and insulation materials improve frequency extension and tonal balance. • Conductor wire fixed by set screw • Specified for cable diameters max. 11.0mm 	
<p>CF-102(R) (2 pcs./Set) 11,000.-</p>	<p>Carbon Fiber Series RCA Connector</p> <ul style="list-style-type: none"> • α (Alpha) OCC rhodium-plated center conductor • α (Alpha) copper alloy rhodium-plated body • Carbon fiber and nonmagnetic stainless steel housing • Copper alloy connector body • Copper alloy set screw • Specified for cable diameters max. 9.3mm • Dimensions: 14.0mm diameter x 54.0mm overall length 	
<p>CF-126(R) (2 pcs./Set) 8,950.-</p>	<p>CF-126(R) High End Performance RCA Connector</p> <ul style="list-style-type: none"> • α (Alpha) OCC rhodium-plated center conductor • α (Alpha) Copper Alloy rhodium-plated body with teflon insulation • Carbon fiber and nonmagnetic stainless steel housing • Termination method: solder • Specified for cable diameters max. 7.3mm • Dimensions: 13.0mm diameter x 39.3mm overall length 	
<p>FP-108(R) (4 pcs/set) 11,800.-/Set</p>	<p>High End Performance RCA Connector</p> <ul style="list-style-type: none"> • α (Alpha) OCC rhodium-plated center conductor • Copper alloy rhodium-plated body • Copper alloy black-painted locking housing • Teflon insulation • Connections: Set screw • Specified for cable diameters up to 9.3mm max. • Dimensions: • 13.8mm ± 0.1mm diameter x 54mm ± 0.1mm overall length 	
<p>FP-120(R) (4 pcs/set) 12,150./Set</p>	<p>High End Performance RCA connector (Filament central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • Phosphor bronze α (Alpha) Filament center pin • Copper alloy body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 12.3mm • Dimensions: 13.9mm ± 0.1 diameter x 59.6mm ± 0.1mm overall length 	
<p>FP-106(R) (4 pcs/set) 10,750.-/Set เลิกผลิต</p>	<p>High End Performance RCA connector (Filament central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • Phosphor bronze α (Alpha) Filament center pin • Copper alloy body and locking collet • Teflon insulation • Connections: Set screw • Specified for cable diameters up to 9.3mm • Dimensions: 13.8mm ± 0.1 diameter x 54mm ± 0.1mm overall length 	




FURUTECH

RCA & XLR

RCA & XLR		
<p>FP-110(G) (4 pcs/set) 8,340.-/Set</p>	<p>High Performance Audio RCA Connectors (PCOCC central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • α (Alpha) OCC Conductor center pin • Copper alloy body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 9.3mm • Dimensions: 13.8mm \pm 0.1 diameter x 54.4mm overall length 	
<p>FT-111(G) (4 pcs/set) 7,450.-/set</p> <p>FT-111(R) (4 pcs/set) 8,350.-/set</p>	<p>High End Performance RCA connector</p> <p>FEATURES</p> <ul style="list-style-type: none"> • Main conductor: <ul style="list-style-type: none"> Plus polarity---One piece Rhodium or 24k gold-plated α (Alpha) Pure copper tube injected with POM resin Minus polarity---One piece Rhodium or 24k gold-plated α (Alpha) Pure copper conductor • Housing: Nonmagnetic Stainless steel. • Insulation Body: Injection Black POM Resin. • Connections: Set screws • End Ring: Nonmagnetic Stainless steel <p>SPECIFICATIONS</p> <ul style="list-style-type: none"> • Specified for core insulation diameters up to 10.0mm • Housing dimensions: 14.0ψ x 26.5mm overall length • Total overall length: 50.6mm approx. 	
<p>FP-160(G) (4 pcs/set) 5,800.-/Set.</p>	<p>High Performance Audio RCA Connectors (Eutectic cast copper alloy central pin/Locking Collet type))</p> <ul style="list-style-type: none"> • Eutectic cast copper alloy α (Alpha) center pin • Copper alloy body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 9.3mm • Dimensions: 14.8mm \pm 0.1 diameter x 52.1mm \pm 0.1mm overall length 	
<p>FP-126(R) (4 pcs/set) 5,600.-/Set</p> <p>FP-126(G) (4 pcs/set) 4,400.-/Set</p>	<p>High Performance Audio RCA Connectors (PCOCC central pin)</p> <ul style="list-style-type: none"> • α (Alpha) OCC Conductor center pin • Copper alloy body and Teflon insulation • Connections: Soldered • Specified for cable diameters up to 7.3mm • Dimensions: 12.6mm \pm 0.1 diameter x 39.3mm overall length 	

FURUTECH

RCA & XLR

RCA & XLR		
<p>FP-104(G) (4 pcs/set)</p>	<p>High Performance Audio RCA Connectors (Eutectic cast brass central pin/Locking Collet type)</p> <ul style="list-style-type: none"> • Eutectic cast brass α (Alpha) center pin • Brass body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 8.3mm • Dimensions: 13mm \pm 0.1 diameter x 5.5mm \pm 0.1mm overall length 	
<p>FP-162(G) 2,700.-/set .</p>	<p>High Performance Audio RCA Connectors (Eutectic cast copper alloy central pin)</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast copper alloy center pin • Copper alloy body and Teflon insulation • Connections: Soldered • Specified for cable diameters up to 7.3mm • Dimensions: 11.9mm \pm 0.1 diameter x 37.3mm overall length 	
<p>FP-3-117(R) (2 pcs/set) 3,700.-/set</p>	<p>High Performance Audio BNC Connector</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast copper alloy center pin • Rhodium-plated copper alloy body with Teflon insulation • Connections: Soldered • Specified for cable diameters up to 8mm • Dimensions: 14mm \pm 0.1 diameter x 43mm \pm 0.1mm overall length 	

FURUTECH

RCA & XLR

<p>CF-601M NCF(R)</p> <p>9,500.-/pcs.</p>	<p>CF-601M NCF(R) XLR: *Rhodium-plated α (Alpha) Pure copper one-piece construction conductor pin injected with heat resistant NCF Liquid Crystal Polymer Resin. *Nylon, fiberglass, nano-sized crystalline piezo ceramic particles, carbon powder and Furutech special "NCF" anti-resonance damping material main body combined in heat resistant NCF Liquid Crystal Polymer Resin. NCF delivers improvements in the depth and focus of the sound stage, harmonics and tonal balance. Low frequencies are cleaner, with a greater sense of definition made possible by a lowered noise floor. *Housing: Multilayer hybrid NCF carbon housing composed of an outer hard clear coat over with another layer of Hybrid NCF Silver plated 3k carbon fiber on a nonmagnetic stainless-steel Housing. The best of damping and insulation materials improve frequency extension and tonal balance.</p>	
<p>CF-602F NCF(R)</p> <p>10,900.-/pcs.</p>	<p>CF-602F NCF(R) XLR: *Rhodium-plated α (Alpha) Pure copper one-piece construction conductors. *Nylon, fiberglass, nano-sized crystalline piezo ceramic particles, carbon powder and Furutech special "NCF" anti-resonance damping material main body combined in heat resistant NCF Liquid Crystal Polymer Resin. NCF delivers improvements in the depth and focus of the sound stage, harmonics and tonal balance. Low frequencies are cleaner, with a greater sense of definition made possible by a lowered noise floor. *Special resonance damping composite release button – formed with stainless steel powder and vibration resistant metal powder. *Chrome-plated brass stamped housing. *NCF material damping clips. *Housing: Multilayer hybrid NCF carbon housing composed of an outer hard clear coat over with another layer of Hybrid NCF Silver plated 3k carbon fiber on a nonmagnetic stainless-steel Housing. The best of damping and insulation materials improve frequency extension and tonal balance.</p>	
<p>CF-601M(R)</p> <p>7,850.-/pcs.</p>	<p>High End Performance CF-601M XLR Connector</p> <ul style="list-style-type: none"> • α (Alpha) Beryllium copper and phosphor bronze Rhodium-plated Conductor • Carbon fiber and nonmagnetic stainless steel housing • Body: PVDF Teflon insulation • Specially designed cable strain relief. • Connections: Soldered • Specified for cable diameters up to 10.0mm (Standard version) • Dimensions: 18.6mm \pm 0.1mm diameter x 65.5mm \pm 0.1mm overall length. 	
<p>CF-602F(R)</p> <p>8,950.-/pcs.</p>	<p>High End Performance CF-602F XLR Connector</p> <ul style="list-style-type: none"> • α (Alpha) Beryllium copper and phosphor bronze Rhodium-plated Conductor • Carbon fiber and nonmagnetic stainless steel housing • Body: PVDF Teflon insulation • Specially designed cable strain relief. • Connections: Soldered • Specified for cable diameters up to 10.0mm (Standard version) • Dimensions: 18.6mm \pm 0.1mm diameter x 77.4mm \pm 0.1mm overall length. 	


FURUTECH

RCA & XLR

<p>FP-601M(R) 6,400.-</p> <p>FP-601M(G) *Dis 5,500.-</p> <p>FP-601M-N1(G) 6,400.- (new)</p>	<p>High End Performance XLR Connectors</p> <ul style="list-style-type: none"> • Beryllium copper and phosphor bronze α (Alpha) Conductor • Copper alloy body and PVDF Teflon insulation • Connections: Soldered • Specified for cable diameters up to 12mm • Dimensions: 19.5mm \pm 0.1 diameter x 48.5mm \pm 0.1mm overall length 	
<p>FP-602F-N1 (R) 8,300.- (new)</p> <p>FP-602F(G) *Dis 6,200.-</p> <p>FP-602F-N1 (G) 7,200.- (new)</p>	<p>High End Performance XLR Connectors</p> <ul style="list-style-type: none"> • Beryllium copper and phosphor bronze α (Alpha) Conductor • Copper alloy body with PVDF Teflon insulation • Connections: Soldered • Specified for cable diameters up to 12mm • Dimensions: 19.5mm \pm 0.1 diameter x 48.5mm \pm 0.1mm overall length 	
<p>FP-701M(G) 1,450.-</p> <p>FP-702F(G) 1,700.-</p>	<p>High Performance XLR Connectors</p> <ul style="list-style-type: none"> • Eutectic cast copper alloy α (Alpha) center pin • Copper alloy body and PBT plus fiberglass insulation • Connections: Soldered • Specified for cable diameters up to 9mm • Dimensions: 21.3mm \pm 0.1 diameter x 63.2mm \pm 0.1mm overall length 	
<p>FP- 705M(R) 2,050.-</p> <p>FP- 706F(R) 2,250.-</p>	<p>4 Pin Balanced XLR Connectors</p> <ul style="list-style-type: none"> • Main conductor: Rhodium-plated α (Alpha) Copper alloy conductor • Insulation with PBT and fiberglass Resin • Housing: Nonmagnetic Zinc/Al alloy and Copper alloy (End shell) • Connections: Soldered • Specified for cable diameters up to 9mm • Dimensions: o FP-705M: 18.8mm \pm 0.1mm diameter x 63.2mm \pm 0.1mm overall length o FP-706F: 19.5mm \pm 0.1mm diameter x 64.2mm \pm 0.1mm overall length 	



FURUTECH

RCA & XLR

RCA & XLR		
<p>CF-BNC(R)</p> <p>9,550.-</p>	<p>CF-BNC (R) High End Performance BNC Connectors</p> <p>RATING Furutech CF-BNC (R) 75Ω BNC Connector Premier Performance and Legendary Build Quality</p> <p>FEATURES Furutech's beautifully finished, beautiful sounding CF-BNC connectors are the result of meticulous engineering and careful audition of various suitable materials. The CF-BNC features an α (Alpha) phosphor bronze conductor and Fluoropolymer PTFE insulation for minimal impedance and a nonmagnetic stainless and carbon fiber finished housing for superior damping.</p> <p>SPECIFICATIONS</p> <ul style="list-style-type: none"> •Main conductor: Nonmagnetic Rhodium-plated α (Alpha) Phosphor bronze conductor •Insulation with Fluoropolymer PTFE Resin •Housing: Nonmagnetic stainless and carbon fiber finished. •Cable Clamp: Copper Alloy. •Specified for wire outer diameters up to 8.0mm •Connections: Soldered <p>Dimensions: Housing: 13.4ψx 22 mm overall length Total overall length: 43.9 mm approx.</p>	

FURUTECH

RCA & XLR

RCA & XLR		
<p>FP-908(R) (2 pcs/set) 8,500.-</p> <p>FP-908(G) (2 pcs/set) 7,450.-</p>	<p>High End Performance PCB mount RCA Socket: FP-908 (R)/(G)</p> <ul style="list-style-type: none"> • α (Alpha) Pure Copper rhodium-plated or gold-plated center conductor • α (Alpha) Lead Free copper alloy rhodium or gold plated body • Central Insulation & Outer Insulation Ring : Nylon + Fiberglass (Red, White) • Conductor fixed by soldering. • α (Alpha) Lead Free copper alloy rhodium or gold plated fixing ring nut • Dimensions: 17.0mm diameter X 21.1mm(H) X 34.5mm overall length 	
<p>FP-901(R) (2 pcs/set) 7,300.-</p>	<p>High End Performance RCA Terminal Sockets</p> <ul style="list-style-type: none"> • Positive/Hot Center Pin: Milled from a single piece of pure copper α (Alpha) conductor with phosphor bronze locking ring • Negative/Cold Conductor: Milled from a single piece of pure copper α (Alpha) conductor • Non-magnetic rhodium-plated materials • Eutectic brass housing (painted black) and 24k gold-plated nut cap • Mounting Materials: Nylon (red or white /outer) and PETF Teflon (white/inner) insulation • Mounting Insulation accommodates chassis panels of any thickness • Connection Type: Soldered <p>Dimensions:</p> <ul style="list-style-type: none"> • Housing---16\pm 0.1mm diameter X19.5mm\pm 0.1mm (Black), • Mounting Insulation set--- Nylon(Red, White)17.3\pm 0.1mm diameter X 7.3mm\pm 0.1mm thick, 39.0mm\pm 0.1mm overall length. 	

FURUTECH

RCA & XLR

<p>FT-903(G) (2 pcs/set) 3,650.-</p> <p>FT-903(R) (2 pcs/set) 3,950.-</p>	<p>High End Performance RCA Sockets</p> <ul style="list-style-type: none"> • Main conductor: 24k gold-plated α (Alpha) pure copper • Insulation Body : Liquid Crystal Polymer Resin • Central color insulation and color ring : Nylon resin (Red/White) • Chassis nut : Plated lead – free copper alloy • Connections : Soldered • Specified for core diameters up to 4.5mm • Dimension : \varnothing 16.0 x 40.0 mm (L) overall length approx. • FT-903 (R) with rhodium plating upon request 	
<p>FP-900G) (2 pcs/set) 3,700.-</p>	<p>High Performance RCA Terminal Sockets</p> <ul style="list-style-type: none"> • Central and Earth conductor- α (Alpha) Eutectic copper alloy Conductor • Non-magnetic direct 24k Gold Plated Conductor • Brass Housing and Nut cap (24k gold plated) • Nylon (red, white) Mounting Insulation set and PETF Teflon (white) Inner insulation. • Mounting Insulation set to accommodate panels of any thickness • Connections: Soldered <p>Dimensions: Housing---14mm\times22.9mm, Mounting Insulation set-- Nylon(Red, White)15mm\times2.7mm, 28.7mm overall length</p>	
<p>FT-909(G) (2 pcs/set) 5,000.-</p> <p>FT-909(R) (2 pcs/set) 5,450.-</p>	<p>FT-909 (R) with rhodium plating upon request.</p> <p>FEATURES</p> <ul style="list-style-type: none"> • Main conductor: 24k gold-plated α (Alpha) Pure copper conductor • Insulation Body: Liquid Crystal Polymer Resin • Central Color Insulation and Color ring: Nylon resin (red/white) • Chassis nut: Plated Lead Free Copper alloy • Connections: Soldered <p>Specified for PCB</p> <p>SPECIFICATIONS</p> <ul style="list-style-type: none"> • Specified for core diameters up to 4.5mm • Dimensions: 20.9 \times 17.35 \times 36.5mm(L) overall length approx. 	

FURUTECH

RCA & XLR

RCA & XLR		
<p>FT-785M(R)</p> <p>2,650.-</p>	<p>FEATURES</p> <ul style="list-style-type: none"> • Main conductor: Rhodium-plated α (Alpha) Pure copper conductor • Housing: Matte black finished Nylon/fiberglass with piezo ceramic resin (SUS plated internal parts) • Pin holder & Conductor Inner insulation: Liquid Crystal Polymer Resin • Connections: Soldered <p>SPECIFICATIONS</p> <p>Dimensions: 32.0 X 27.0 x 32.7mm (H) overall height</p>	
<p>FT-786F (R)</p> <p>2,800.-</p>	<p>FT-786F(R) XLR Female Sockets Premier Performance and Legendary Build Quality</p> <p>FEATURES</p> <ul style="list-style-type: none"> • Main conductor: Rhodium-plated α (Alpha) Pure copper conductor • Housing: Matte black finished Nylon/fiberglass with piezo ceramic resin (SUS plated internal parts) • End cover: Liquid Crystal Polymer Resin • Connections: Soldered <p>SPECIFICATIONS</p> <p>Dimensions: 32.0 x 27.0 x 36.9mm overall height</p>	