

# FURUTECH

## Receptacle & Cover



<p><b>GTX-D NCF(R)</b></p> <p><b>16,700.-</b></p> <p><b>GTX-S NCF(R)</b></p> <p><b>14,200.-</b></p>	<p><b>GTX-NCF(R): 20A 125V</b>  <b>Furutech's Top-Tier GTX –S NCF Receptacles</b></p> <p>Furutech's Ultimate AC Receptacle Series</p> <ul style="list-style-type: none"> <li>- Rhodium-plated <math>\alpha</math> (Alpha) Pure Copper Conductor (0.8mm)</li> <li>Nonmagnetic stainless conductor spring system</li> <li>- Body material: Nylon/fiberglass with anti-resonance nano-sized crystalline, piezo ceramic particles and carbon.</li> <li>- Cover material: Polycarbonate with a special anti-resonance nano-sized crystalline material "NCF"</li> <li>- Parts set with nonmagnetic 2.0mm-thick stainless brace plate</li> <li>- Specified for wire diameters of 4 mm (set screw)</li> <li>- Dimensions: 104.0 mm (L) x 47.2 mm (W) x 28.0 mm (H)</li> <li>- Total attention to detail and build quality extends right down to a specially designed patent-pending conductor pressure plate that increases contact area</li> <li>- Furutech spade terminal FP-205 recommended for 10 AWG wire</li> </ul>	<p></p> 
<p><b>GTX-D(R)</b></p> <p><b>14,200.-</b></p> <p><b>GTX-D(G)</b></p> <p><b>12,300.-</b></p>	<p>Furutech's Top-Tier GTX Receptacles</p> <ul style="list-style-type: none"> <li>• Rhodium or gold-plated <math>\alpha</math> (Alpha) Pure Copper Conductor (0.8mm)</li> <li>• Nonmagnetic stainless conductor spring system</li> <li>• Body material: Nylon/fiberglass with piezo ceramic and carbon damping material</li> <li>• Cover material: Polycarbonate</li> <li>• Parts set with nonmagnetic 2.0mm-thick stainless brace plate</li> <li>• Specified for wire diameters of 4 mm (set screw)</li> <li>• Dimensions: 104.0 mm (L) x 47.2 mm (W) x 28.0 mm (H)</li> <li>• Total attention to detail and build quality extends right down to a specially designed patent-pending conductor pressure plate (see below) that increases contact area</li> <li>• Furutech spade terminal FP-209 recommended for 10 AWG wire</li> </ul>	
<p><b>FPX-(R)</b></p> <p><b>7,200.-</b></p> <p><b>FPX-(G)</b></p> <p><b>6,000.-</b></p> <p><b>FPX-(Cu)</b></p> <p><b>4,250.-</b></p>	<p>High Performance Duplex Receptacles</p> <p>All non-magnetic <math>\alpha</math> (Alpha) Phosphor bronze Conductor  All models c(UL) approved</p> <p>Unique pin insert construction ensures increased contact areas, stable transmission and the tightest contacts in the Audio industry and they won't scratch or mark the plating on male AC connectors! Accommodates cable diameters from 10 AWG to 24 AWG.  Dimensions: 104.2mm×33.5mm (L×W), 28.2mm thick.  Materials: Main body: Nylon and Fiber Glass  Cover: White polycarbonate for FPX- (R) and (G), Black for FPX- (Cu)  Connections: Set-screw  Non-magnetic Rhodium, 24k Gold or Non plated Phosphor Bronze conductor (t: 0.8 mm)</p>	

# FURUTECH

## Receptacle & Cover

**GTX Wall Plate**  
9,900.-

High Performance Wall Plate for Duplex /Single Outlets

- Beautifully crafted special grade aluminum CNC processed chassis effectively shields against RFI (Radio Frequency Interference).
- Material thickness: chassis plate 13.0mm
- Finished with an extremely effective nonresonant coating.
- Includes Special Teflon damping foil and SUS Receptacle fixed screw 4 pcs (M3) and SUS Plate fixed screw 2 pcs (50mm overall length).
- Suitable for use with GTX-D or GTX-S receptacle and 104-D or 104-S carbon fiber finished cover.
- Dimensions: 135.0mm (L) x 86.0mm (W) x 13.0mm(H) - 0/+0.3mm



**Outlet cover 106-D Plus NCF**  
9,900.-

**Outlet cover 106-S Plus NCF**  
9,900.-

**106-D Plus NCF**  
NCF Damper and EMC Neutralizing Outlet Cover

**SPECIFICATIONS**  
Formed from a hybrid NCF 3K diagonal pattern carbon fiber sheet over an EMC neutralizing multi-layered NCF glass fiber base plate with a special NCF coating material finish - for the most effective damping and electromagnetic interference minimizing EMC faceplate available.  
New Improved Outlet Cover for GTX-D NCF / GTX-D / FPX duplex receptacle designs.  
Suggested torque: 10Kgf-cm (0.98N·m) max.  
Cover overall size: 72.1 x 116.4 x 5.3 mm±0.3mm  
Net Weight: 25.9g approx. (± 1.5g)  
Stainless fixed screw size: M4 X 12mm (L)  
\*\*\*EMC (Electro Magnetic Compatibility)



**Outlet cover 102-D**  
2,300.-

**Outlet cover 102-S**  
2,300.-

New and greatly improved Pure Transmission 102-D Duplex Receptacle Cover Plate

102 series:  
Stainless Fixed Screw/Size : M4 X 12mm(L)  
Stainless Cover /Size : 71X116 mm(t : 1.2mm)  
With "FO-Q" vibration damping material  
c(UL) Approved

