






Connectors(Power & IEC)

1	<p>FI-25(R)-N1 5,650.- /pcs.</p> <p>FI-25(G)-N1 4,240.-/ pcs.</p>	<p>High End Performance IEC connectors</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor bronze Conductor • Earth (Ground) Jumper System • Nylon/fiberglass front body • polycarbonate shell • Specified for cable diameters of 6mm to 17mm • Dimensions: Body length 43.9mm x 39mm diameter x 76mm overall length • Rated: 15A/125V and 10A/250V 	
2	<p>FI-25M(R)-N1 5,650.-/pcs.</p> <p>FI-25M(G)-N1 4,240.-/ pcs.</p>	<p>High End Performance Power connectors</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductor • Earth (Ground) Jumper System • Nylon/fiberglass front body • polycarbonate shell • Specified for cable diameters of 6mm to 17mm • Dimensions: Body length 40.2mm x 39mm diameter x 74mm overall length • Rated: 15A/125V 	
3	<p>FI- 11 (G) 2,510.-/pcs.</p> <p>FI- 11 (Ag) 2,825.-/pcs.</p> <p>FI- 11 (Cu) 1,880.-/pcs.</p>	<p>High Performance IEC connectors</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor bronze Conductor • Earth (Ground) Jumper System • Nylon/fiberglass front body, polycarbonate shell • Specified for cable diameters of 6.6mm to 16mm (With a longer screw up to 20mm) • Dimensions: Body length 43.9mm x 39mm diameter x 76mm overall length • Rated: 15A/125V and 10A/250V 	 
4	<p>FI- 11 M(G) 2,510.-/ pcs.</p>	<p>High Performance Power connector</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductor • Earth (Ground) Jumper System • Nylon/fiberglass front body • Polycarbonate shell • Specified for cable diameters of 6.6mm to 16mm (With a longer screw up to 20mm) • Dimensions: Body length 40.2mm x 39mm diameter x 74mm overall length • Rated: 15A/125V 	
5	<p>FI- 11 M(Cu) 1,880.-/pcs.</p>	<p>High Performance Power connector</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductor • Earth (Ground) Jumper System • Nylon/fiberglass front body • Polycarbonate shell • Specified for cable diameters of 6.6mm to 16mm (With a longer screw up to 20mm) • Dimensions: Body length 40.2mm x 39mm diameter x 74mm overall length • Rated: 15A/125V 	

6	<p>FI-15E(R) 2,510.-/pcs.</p> <p>FI-15E(G) 1,880.-/pcs.</p>	<p>High Performance IEC Connectors</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductor • Earth (Ground) Jumper System • Nylon and fiberglass housing • Specified for cable diameters of 6.6mm to 13mm • Dimensions: 31.0mm x 33.3mm x 72.0mm overall length • Rated: 15A/125V and 10A/250V 	
7	<p>FI-15ME(R) 2,510.-/pcs.</p> <p>FI-15ME(G) 1,880.-/pcs.</p>	<p>High Performance Power Connectors</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductor • Earth (Ground) Jumper System • Nylon and fiberglass housing • Specified for cable diameters of 6.6mm to 13mm • Dimensions: 31.0mm x 33.3mm x 72.0mm overall length • Rated: 15A/125V 	
8	<p>FI-32(R) 8,160.-/pcs.</p> <p>FI-32(G) 5,960.-/pcs.</p>	<p>High End Performance 16A/250V&20A/125V IEC connectors</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor bronze Conductor • Earth (Ground) Jumper System • Material: Nylon/fiberglass • Polycarbonate shell • Specified for cable diameters of 6.6mm to 18.0mm • Dimensions: Body length 40.8mm x 39mm diameter x 74mm overall length • Rated: 20A/125V and 16A/250V 	
9	<p>FI-32M(R) 8,160.-/pcs.</p> <p>FI-32M(G) 5,960.-/pcs.</p>	<p>High End Performance 20A/125V Power connectors</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductor • Earth (Ground) Jumper System • Nylon/fiberglass front body • Polycarbonate shell • Specified for cable diameters of 6.6mm to 18.0mm • Dimensions: Body length 40.2mm x 39mm diameter x 74mm overall length • Rated: 20A/125V 	
10	<p>FI-31M(G) 5,650.-/pcs.</p>	<p>High Performance 20A/125V Power connector</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductors • Earth (Ground) Jumper System. • Nylon/fiberglass front body • polycarbonate shell • Specified for cable diameters of 6.6mm to 20.0mm • Dimensions: Body length 40.2mm x 39mm diameter x 74mm overall length • Rated: 20A/125V 	
11	<p>FI-31(G) 5,650.-/ pcs.</p>	<p>High Performance 16A/250V&20A/125V IEC connector</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor bronze Conductor • Earth (Ground) Jumper System. • Nylon/fiberglass front body • polycarbonate shell • Specified for cable diameters of 6.6mm to 20.0mm • Dimensions: Body length 40.8mm x 39mm diameter x 74mm overall length • Rated: 20A/125V and 16A/250V 	