



Inlets, Receptacles and Power Distributors

1	<p>FI-33(R) 5,020.-/pcs.</p> <p>FI-33(G) 4,080.-/pcs.</p>	<p>High End Performance 16A 250V / 20A 125V IEC Inlets</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductor • Material: Nylon/fiberglass • Specified for wire diameters of 4mm (set screw) • Dimensions: 60.4mm(W) x 30.4mm(D) x 38.7mm(H) • Rated: 20A/125V and 16A/250V 	
2	<p>FI-09(G) 3,450.-/pcs.</p> <p>FI-09(R) 4,390.-/pcs.</p>	<p>High End Performance IEC Inlets</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductor • Materials: Nylon/fiberglass • Specifications: Accommodates cable diameters to 4mm (set-screw) • Dimensions: 60.0mm (W) x 30.2mm (D) x 36.2mm(H) • Rated: 15A/250V 	
3	<p>AC-INLET (R) 690.-/pcs.</p> <p>AC-INLET (G) 500.-/pcs.</p>	<p>High Performance IEC Inlets</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic (low temperature) cast brass Conductor • PBT and fiberglass housing • Connection: Soldered • Dimensions: 49.45mm(W)x 22.0mm(D)x 27.1mm (H) • Rated: 15A/125V and 10A/250 	
4	<p>FI-10(R) 1,440.-/pcs.</p> <p>FI-10(G) 1,100.-/pcs.</p>	<p>High Performance IEC Inlets</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic (low temperature) cast brass Conductor • Nylon and fiberglass housing • Connection: Set screw • Dimensions: 50.9mm (W) x 24.1mm (D) x 28.8 (H) • Rated: 15A/250V 	
5	<p><u>New 2007</u></p> <p>FT-D20A (R) 8,285.-/pcs.</p> <p>FT-D20A (G) 6,200.-/pcs</p>	<p>High End Performance 20A125V Duplex Receptacle</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor Bronze Conductor(t : 0.8mm) • Material: Nylon/fiberglass body and Polycarbonate cover; parts fixed with a 2.0mm thick Stainless brace plate • Specified for wire diameters of 4mm (set screw) • Dimensions: 104.0mm (L) x 47.2mm (W) x 28.0mm(H) 	

6	<p>New 2007</p> <p>FT-S20A (R) 6,590.-/pcs.</p> <p>FT-S20A (G) 5,585.-/pcs.</p>	<p>High Performance 20A125V Single Receptacle</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor Bronze Conductor(t : 0.8mm) • Material: Nylon/fiberglass body and Polycarbonate cover; parts fixed with a 2.0mm thick stainless brace plate • Specified for wire diameters of 4mm (set screw) • Dimensions: 104.0mm (L) x 47.2mm (W) x 28.0mm(H) 	
7	<p>New 2007</p> <p>FP-15A (G)-N1 3,695.-/pcs.</p> <p>FP-15A (Cu)-N1 2,825.-/pcs.</p> <p>FP-15A (R) - N1 4,730.-/pcs.</p>	<p>High Performance 15A 125V Duplex receptacle</p> <ul style="list-style-type: none"> • 0.8mm thick α (Alpha) Phosphor bronze Conductor • Nylon/fiberglass front body, Polycarbonate shell, parts fixed with a 1.2mm thick stainless brace plate • Specified for wire diameters up to 3.2mm solid-core and 3.0mm stranded • Dimensions: Body 35.5mm (W) x 28.2mm (D) x 104.2mm overall length • Rated: 15A/125V 	
8	<p>e-TP-60 17,595.-/ pcs.</p>	<p>AC Power Distributor + GC-303</p> <ul style="list-style-type: none"> • GC-303 EMI-Absorbent Internal Coating • Outputs: 6 Outlets • Input: 15A IEC • Dimensions: 200mm (W) x 130mm (D) x 60mm (H) • Rated: 15A/125V • Net Weight: 0.94kg 	
9	<p>e-TP-80 30,750.-/ pcs.</p>	<p>AC Power Filter + GC-303</p> <ul style="list-style-type: none"> • GC-303 EMI-Absorbent Internal Coating plus EMI noise filter • Outputs: 8 outlets (4 filtered, 4 non-filtered) • Input:15A IEC • Overall Size: 400mm (W) x 130mm (D) x 60mm (H) • Rated:15A/125V • Net Weight: 1.72Kgs 	
10	<p>e-TP60/20 37,660.-/ pcs.</p>	<p>AC Power Distributor (20A/125V)</p> <ul style="list-style-type: none"> • Axial Locking System • GC-303 Technology • Includes one G-762-18 15A/20A power cord in the purchase price • Outputs: 6 Outlets • Input: 20A IEC • Dimensions: 225mm (W) x 130mm (D) x 60mm (H) • Rated: 20A/125V • Net Weight: 1.15kgs 	

11	<p>e-TP4+4 94,150.-/pcs.</p>	<p>Twin Power Distributor (20A/125V and 15A/125V)</p> <ul style="list-style-type: none"> • Axial Locking System • GC-303 Technology • Chassis CNC machined from solid aluminum and equipped with mounting spikes • Special Vibration Dampener Coating. • Outputs: 8 Outlets (4/20A + 4/15A) • Inputs: 20A IEC and separate 15A IEC • Dimensions: 297mm (W) x 130mm (D) x 56mm (H) • Rated: 20A/125V and 15A/125V • Net Weight: 3.15Kgs 	
12	<p>e-TP609 61,510.-/pcs.</p>	<p>AC Power Distributor (High End Performance)</p> <ul style="list-style-type: none"> • Features Axial Locking System • GC-303 EMI-Absorbent Internal Coating • Chassis CNC machined from solid aluminum and equipped with mounting spikes • Special Vibration Dampener Coating. • Outputs: 6 Outlets • Input: 15A/125V IEC • Dimensions: 246mm (W) x 130mm (D) x 56mm (H) • Rated: 15A/125V • Net Weight: 2.85Kgs 	

Remark : (G) = 24k Gold Plated, (R) = Rhodium Plated, (Ag) = Silver Plated, (Cu) = Non-Plated.

All metallic parts are treated with

FURUTECH Alpha Cryogenic and Demagnetizing Treatment

FURUTECH reserves the right to change product specifications without prior notice.

FURUTECH CO., LTD.

www.furutech.com

service@Furutech.com

Make A More Powerful Connection with Furutech!