











Accessories (XLR, RCA, Spade, Banana, BNC Connectors)

1	<p>FP-110(G) 5,335.-/set</p>	<p>High Performance PCOCC Central PIN RCA connector</p> <ul style="list-style-type: none"> • α (Alpha) OCC Conductor center pin • Brass body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 9.3mm • Dimensions: 13.8mm ± 0.1mm diameter x 54.4mm ± 0.1mm overall length 	
2	<p>FP-126(G) 565.-/pcs.</p>	<p>High Performance PCOCC Central PIN RCA connector</p> <ul style="list-style-type: none"> • α (Alpha) OCC Conductor center pin • Brass body with Teflon insulation • Connections: Soldered • Specified for cable diameters up to 7.3mm • Dimensions: 12.6mm ± 0.1mm diameter x 39.3mm ± 0.1mm overall length 	
3	<p>FP-160(G) 3,765.-/set 895.-/pcs.</p>	<p>High Performance RCA connector</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast brass center pin • Brass body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 9.3mm • Dimensions: 14.8mm ± 0.1mm diameter x 52.1mm ± 0.1mm overall length 	
4	<p>FP-104(G) 3,765.-/set 895.-/pcs.</p>	<p>High Performance RCA connector</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast brass center pin • Brass body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 8.3mm • Dimensions: 13mm ± 0.1mm diameter x 51.5mm ± 0.1mm overall length 	
5	<p>FP-162(G) 250.-/pcs.</p>	<p>High Performance RCA connector</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast brass center pin • Brass body with Teflon insulation • Connections: Soldered • Specified for cable diameters up to 7.3mm • Dimensions: 11.9mm ± 0.1mm diameter x 37.3mm overall length 	
6	<p>FP-3-117(R) 2,135.-/set 1,020.-/pcs.</p>	<p>High Performance Audio BNC Connector</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast brass center pin • Rhodium-plated brass body with Teflon insulation • Connections: Soldered • Specified for cable diameters up to 8mm • Dimensions: 14mm ± 0.1mm diameter x 43mm ± 0.1mm overall length 	

7	<p>FP-203(R) 2,070.-/set 485.-/pcs. FP-203(G) 1,760.-/ set 410.-/pcs.</p>	<p>High Performance Audio Spade Terminals</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductors • Connections: Set screw or soldered • Specified for cable diameters up to 6mm • Dimensions: Space between Conductor: 8.2mm 12.9mm ± 0.1mm (W) x 24mm ± 0.1mm overall length 	
8	<p>FP-201(R) 3,765.- /set FP-201(G) 2,825.-/set</p>	<p>High Performance Audio Spade Terminals</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductors • Connections: Set screw or soldered • Specified for cable diameters up to 6mm • Dimensions: Space between Conductor: 8.2mm 12.9mm ± 0.1mm (W) x 40mm ± 0.1mm overall length 	
9	<p>FP-202(R) 4,390.-/set 1,035.-/pcs. FP-202(G) 3,640-/set 860.-/pcs.</p>	<p>High Performance Audio Banana Connectors</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast brass pins • Connections: Set-screw • Specified for cable diameters up to 7mm • Dimensions: 12mm ± 0.1mm diameter x 26.7mm ± 0.1mm (H) x 46mm ± 0.1mm overall length 	
10	<p>FP-200B(G) 485.-/pcs.</p>	<p>High Performance Audio Banana Connectors</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor bronze pins • Connections: Set-screw • Specified for cable diameters up to 5mm • Dimensions: Housing: 11.0mm ± 0.1mm diameter x 30.3mm ± 0.1mm length ,Conductor pin: 4.5mm ± 0.1mm diameter x 19.7mm ± 0.1mm length, 50.0mm ± 0.1mm overall length. 	

Remark : (G) = 24k Gold Plated, (R) = Rhodium Plated, (Ag) = Silver Plated, (Cu) = Non-Plated.

All metallic parts are treated with

FURUTECH Alpha Cryogenic and Demagnetizing Treatment

FURUTECH reserves the right to change product specifications without prior notice.

FURUTECH CO., LTD.


www.furutech.com

service@Furutech.com

Make A More Powerful Connection with Furutech!

Accessories (XLR, RCA, Spade, Banana, BNC Connectors)

1	<p>FP-601M (R) 3,845.-/pcs.</p> <p>FP-601M (G) 3,140.-/pcs.</p>	<p>High End Performance XLR connectors(Male)</p> <ul style="list-style-type: none"> • α (Alpha) Beryllium copper and phosphor bronze Conductor • Brass body with PVDF Teflon insulation • Connections: Soldered • Specified for cable diameters up to 12mm • Dimensions: 19.5mm ± 0.1mm diameter x 48.5mm ± 0.1mm overall length 	
2	<p>FP-602F (R) 4,550.-/pcs.</p> <p>FP-602F (G) 3,530.-/pcs.</p>	<p>High End Performance XLR connectors(Female)</p> <ul style="list-style-type: none"> • α (Alpha) Beryllium copper and phosphor bronze Conductor • Brass body with PVDF Teflon insulation • Connections: Soldered • Specified for cable diameters up to 12mm • Dimensions: 19.5mm ± 0.1mm diameter x 54.2mm ± 0.1mm overall length 	
3	<p>FP-701M(G) 628.-/pcs.</p> <p>FP-702F(G) 705.-/pcs.</p>	<p>High Performance XLR connectors(Male/Female)</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic cast brass center pin • Brass body with PBT and fiberglass insulation • Connections: Soldered • Specified for cable diameters up to 9mm • Dimensions: <ul style="list-style-type: none"> ○ FP-701M: 21.3mm ± 0.1mm diameter x 63.2mm ± 0.1mm overall length ○ FP-702F: 19.5mm ± 0.1mm diameter x 64.2mm ± 0.1mm overall length 	
4	<p>FP-106(R) 6,900.-/set 1,725.-/pcs.</p>	<p>High End Performance Filament Central PIN RCA connector</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor bronze <i>Filament</i> center pin • Brass body and locking collet • Teflon insulation • Connections: Set screw • Specified for cable diameters up to 9.3mm • Dimensions: 13.8mm ± 0.1mm diameter x 54mm ± 0.1mm overall length 	
5	<p>FP-120F (R) 7,030.-/set 1,757.-/pcs.</p>	<p>High End Performance Filament Central PIN RCA connector</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor bronze <i>Filament</i> center pin • Brass body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 12.3mm • Dimensions: 13.8mm ± 0.1mm diameter x 61.2mm ± 0.1mm overall length 	

6	<p>FP-101(G) 5,960.-/set 1,490.-/pcs.</p>	<p>High End Performance Filament Central PIN RCA connector</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor bronze <i>Filament</i> center pin • Brass body and locking collet • Teflon insulation • Connections: Soldered • Specified for cable diameters up to 9.3mm • Dimensions: 13.8mm \pm 0.1mm diameter x 54mm \pm 0.1mm overall length 	
---	--	---	---

Remark : (G) = 24k Gold Plated, (R) = Rhodium Plated, (Ag) = Silver Plated, (Cu) = Non-Plated.

All metallic parts are treated with

FURUTECH Alpha Cryogenic and Demagnetizing Treatment

FURUTECH reserves the right to change product specifications without prior notice.

FURUTECH CO., LTD.

www.furutech.com

service@Furutech.com

Make A More Powerful Connection with Furutech!