










## OEM and DIY Products

1	<p><b>T-13A</b> 3,765.-/pcs.</p>	<p><b>High End Performance Fuse</b>            *Conductor : <math>\alpha</math> (Alpha) Pure Silver conductor            *Rhodium Plated            Length: 25mm            Diameter: 6.4mm            Amperage: 13A            *Package : 1 pcs /Set</p>	
2	<p><b>New 2007</b>  <b>High Performance Outlet cover 102-S</b>  <b>1,440.-/pcs.</b>  <b>Outlet cover 102-D</b>  <b>1,440.-/pcs.</b>  <b>High End Performance Outlet Cover 103-S</b>  <b>4,265.-/pcs.</b>  <b>Outlet Cover 103-D</b>  <b>4,265.-/pcs.</b></p>	<p><b>New Receptacle Covers for FP-15A-N1 / FP-20A-N1/ FT-D20A / FT-S20A series (Available in both single and duplex receptacle designs).</b>  <b>102 series:</b> Stainless Fixed Screw/Size : M4 X 12mm(L)            Stainless Cover /Size : 71X116 mm(t : 1.2mm)            With "FO-Q" vibration damping material  <b>103 series:</b> Stainless Fixed Screw/Size : # M4 X 12mm(L)            Carbon fiber and Grass fiber finished Brass cover            Cover Size : 71X116 mm(t : 2.3mm <math>\pm</math> 0.1mm)</p>	
3	<p><b>FP-001 Tool</b> 3,765.-/set</p>	<ul style="list-style-type: none"> <li><b>Screw driver Set</b></li> </ul>	
4	<p><b>S-070</b> 4,080.-/ Roll</p>	<p><b>High Performance Solder 4% fine silver content (250g/Reel)</b>            *Construction : 96% Sn + 4% Ag. (Lead Free)            *Rosin Type: Ersin 362Flux , 5 core            *Flux Temp.: 220°C Approx.            *Diameter : 0.70 mm            *Package : 250 grams /Spool (RoHS compliance)</p>	
5	<p><b>GS Series Crimp Sleeves</b> 3,140.-/ set @series</p>	<p><b>High Performance Crimp Sleeves</b>            * 24k Gold plated non-magnetic <math>\alpha</math>- Conductor            * Material: Pure Copper Pipe            GS-11P (I.D. :1.1mm X Overall length:6mm) for 20 AWG            GS-21P (I.D. :2.1mm X Overall length:10mm) for 14 AWG            GS-28P (I.D. :2.8mm X Overall length:10mm) for 12 AWG            GS-35P (I.D. :3.5mm X Overall length:10mm) for 10 AWG            GS-46P (I.D. :4.6mm X Overall length:10mm) for 8 AWG            GS-83P (I.D. :8.3mm X Overall length:20mm) for 4 AWG            GS-90P (I.D. 9.0mm X Overall length:20mm L) for 2 AW</p>	

6	<p><b>FP-681M(R)/FP-682F(R)</b> 2,825.-/pcs.</p> <p><b>FP-681M(G)/FP-682F(G)</b> 1,880.-/pcs.</p>	<p><b>High End Performance XLR Sockets</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Beryllium copper and phosphor bronze Conductor</li> <li>• Brass body and PVDF Teflon insulation</li> <li>• Zn-Mg Alloy Casting Housing</li> <li>• Connections: Soldered</li> <li>• Dimensions: <ul style="list-style-type: none"> <li>○ FP-681M: Housing---36.5± 0.1mm diameter X21.2mm± 0.1mm,33.7mm± 0.1mm overall length</li> <li>○ FP-682F: Housing---36.5± 0.1mm diameter X30.2mm ± 0.1mm,39.3mm ± 0.1mm overall length</li> </ul> </li> </ul>	
7	<p><b>FP-781M(G)</b> 565.-/pcs.</p> <p><b>FP-782F(G)</b> 625.-/pcs.</p>	<p><b>High Performance XLR Sockets</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Eutectic cast brass center pin</li> <li>• Brass body and PBT plus fiberglass insulation</li> <li>• Connections: Soldered</li> <li>• Zn-Mg Alloy Casting Housing</li> <li>• Dimensions: <ul style="list-style-type: none"> <li>○ FP-781M: Housing---36.6± 0.1mm X22.3mm± 0.1mm,27.5mm± 0.1mm overall length</li> <li>○ FP-782F: Housing---36.6± 0.1mm X27.1mm± 0.1mm,43.9mm± 0.1mm overall length</li> </ul> </li> </ul>	
8	<p><b>FP-704(G)</b> -(Stereo) 750.-/pcs.</p> <p><b>FP-703(G)</b>- (Mono) 625.-/pcs.</p>	<p><b>High Performance Phone Jackets</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Eutectic cast brass center pin</li> <li>• Brass ending housing with PBT and fiberglass insulation</li> <li>• Specified for cable diameters up to 8mm</li> <li>• Connections: Soldered</li> <li>• Zn-Mg Alloy Casting body housing</li> <li>• Dimensions: <ul style="list-style-type: none"> <li>○ FP-703: Housing---17.8± 0.1mm diameter X65.8mm± 0.1mm,97.3mm± 0.1mm overall length</li> <li>○ FP-704: Housing---17.8± 0.1mm diameter X65.8mm± 0.1mm,97.8mm± 0.1mm overall length</li> </ul> </li> </ul>	
9	<p><b>FP-800B(G)</b> 4,080.-/set</p> <p><b>FP-800B(R)</b> 5,020.-/set</p>	<p><b>High End Performance short Binding posts (2 Pcs/ Set)</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Phosphor bronze Conductor</li> <li>• Eutectic Brass Housing</li> <li>• Nylon(red, white) and Polycarbonate(clear) insulation</li> <li>• Connections: Soldered or Set-screw</li> <li>• Specified for core diameters up to 4.5mm</li> <li>• Dimensions: Housing---15.6± 0.1mm diameter X22mm± 0.1mm, Insulation--- Polycarbonate ( Clear ) 19.3± 0.1mm diameter X7.3mm± 0.1mm ,49.7 mm± 0.1mm overall length.</li> </ul>	

10	<p><b>FP-801B(G)</b> (2 Pcs/ Set) 4,390.-/set</p> <p><b>FP-802B(G)</b> (4 Pcs/ Set) 8,160.-/set</p>	<p><b>High End Performance short billet Binding post series</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Phosphor bronze Conductor</li> <li>• Eutectic Brass Housing</li> <li>• Nylon(red, white) and Polycarbonate(clear) insulation</li> <li>• Connections: Soldered or Set-screw</li> <li>• Specified for core diameters up to 4.5mm</li> <li>• Dimensions: <ul style="list-style-type: none"> <li>○ FP-801: Housing---15.6± 0.1mm diameter X22mm± 0.1mm,Insulation--- Polycarbonate ( Clear ) 56X18.9X17.3mm± 0.1mm ,49.7 mm± 0.1mm overall length</li> <li>○ FP-802: Housing---15.6± 0.1mm diameter X22mm± 0.1mm,Insulation--- Polycarbonate ( Clear ) 98.1X18.9X17.3mm± 0.1mm ,49.7 mm± 0.1mm overall length</li> </ul> </li> </ul>	 
11	<p><b>FP-805B(G)</b> 4,390.-/set</p> <p><b>FP-805B(R)</b> 5,335.-/set</p>	<p><b>High End Performance long Binding posts (2 Pcs/ Set)</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Phosphor bronze Conductor</li> <li>• Eutectic Brass Housing</li> <li>• Nylon(red, white) and Polycarbonate(clear) insulation</li> <li>• Connections: Soldered or Set-screw</li> <li>• Specified for core diameters up to 4.5mm</li> <li>• Dimensions: Housing---15.6± 0.1mm diameter X22mm± 0.1mm, Insulation--- Polycarbonate ( Clear ) 19.3± 0.1mm diameter X7.3mm± 0.1mm , 0.1 mm ± 0.1mm overall length</li> </ul>	
12	<p><b>FP - 901 (G)</b> 3,890.-/set</p> <p><b>FP - 901 (R)</b> 4,895.-/set</p>	<p><b>High End Performance RCA Terminal Sockets (2 Pcs/ Set)</b></p> <ul style="list-style-type: none"> <li>• Positive/Hot Center Pin: Milled from a single piece of <math>\alpha</math> (Alpha) pure copper conductor with phosphor bronze locking ring</li> <li>• Negative/Cold Conductor: Milled from a single piece of <math>\alpha</math> (Alpha) pure copper conductor</li> <li>• Non-magnetic 24k gold or Rhodium plated materials</li> <li>• Eutectic brass housing (painted black)and 24k gold-plated nut cap</li> <li>• Mounting Materials: Nylon (red or white /outer) and PETF Teflon (white/inner) insulation</li> <li>• Mounting Insulation accommodates chassis panels of any thickness</li> <li>• Connection Type: Soldered</li> <li>• Dimensions: Housing---16± 0.1mm diameter X19.5mm± 0.1mm (Black), Mounting Insulation set--- Nylon(Red, White)17.3± 0.1mm diameter X total 7.3mm± 0.1mm, 39.0mm± 0.1mm overall length</li> </ul>	 

**FP - 900 (G)**  
2,510.-/set

**High Performance RCA Terminal Sockets (2 Pcs/ Set)**

- Both positive and Negative conductors are made from  $\alpha$  (Alpha) Eutectic Brass.
- Non-magnetic 24k Gold direct Plated Conductor
- 24k gold plated Brass Housing and Nut cap
- Mounting Materials: Nylon (red or white/outer) and PETF Teflon (white/inner) insulation
- Mounting Insulation accommodates chassis panels of any thickness
- Connection Type: Soldered
- Dimensions: Housing---14± 0.1mm diameter X22.9mm± 0.1mm, Mounting Insulation set--- Nylon(Red, White)15.0± 0.1mm diameter X total 2.7mm± 0.1mm, 28.7mm± 0.1mm overall length



**Remark : (G) = 24k Gold Plated, (R) = Rhodium Plated, (Ag) = Silver Plated, (Cu) = Non-Plated.  
B = Painted Black.**

*All metallic parts are treated with*

*FURUTECH Alpha Cryogenic and Demagnetizing Treatment*

FURUTECH reserves the right to change product specifications without prior notice.

**FURUTECH CO., LTD.**

[www.furutech.com](http://www.furutech.com)

[service@Furutech.com](mailto:service@Furutech.com)

*Make A More Powerful Connection with Furutech!*