












## Bulk Cable Products

1	<p><b>FA-13S-50</b> 1,660.-/ M.</p>	<p><b>Bulk Cables • Interconnect Balanced Cable • Solid-Core</b></p> <ul style="list-style-type: none"> <li>• Conductor: 1.3mm diameter solid-core <math>\alpha</math> (Alpha) <math>\mu</math>-OFC Conductor</li> <li>• Insulation: Polypropylene (Red/White) 2.4mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Shield: 0.12mm braided <math>\alpha</math> (Alpha) Conductor</li> <li>• Sheath: Flexible PVC (Dark Green) approx. 8mm diameter (16 AWG)</li> <li>• Package: 50m/Reel</li> </ul>	
2	<p><b>FA-220-50</b> 2,550.-/ M.</p>	<p><b>Bulk Cables • Interconnect Balanced Cable</b></p> <ul style="list-style-type: none"> <li>• Conductor: 80-strand <math>\alpha</math> (Alpha) -OCC Conductor 0.18mm diameter</li> <li>• Insulation: Polypropylene (Red/White) 2.4mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Shield: 0.12mm braided <math>\alpha</math> (Alpha) Conductor</li> <li>• Sheath: Flexible PVC (Dark Green) approx. 9mm diameter (14 AWG)</li> <li>• Package: 50m/Reel</li> </ul>	
3	<p><b><math>\mu</math> - P2.1-50</b> 1,990.-/ M</p>	<p><b>Bulk Cables • Interconnect Balanced Cable</b></p> <ul style="list-style-type: none"> <li>• Conductor: 30-strand <math>\alpha</math> (Alpha)- OCC Conductor 0.18mm diameter</li> <li>• Insulation: Polypropylene (Red/White) 2.6mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Shield: 0.12mm braided <math>\alpha</math> (Alpha) Conductor</li> <li>• Sheath: Flexible PVC (Dark Green) approx. 8mm diameter (18 AWG)</li> <li>• Package: 50m/Reel</li> </ul>	
4	<p><b>FX-<math>\alpha</math> Ag-50</b> 2,490.-/M.</p>	<p><b>Bulk Cables • Interconnect Coaxial Cable (Pure Silver Wire with Teflon Insulation)</b></p> <ul style="list-style-type: none"> <li>• Conductor: 7 strands (Alpha) pure silver conductor 0.18mm diameter</li> <li>• Insulation: Teflon plus air-foam polyethylene 3mm diameter</li> <li>• Shield-1: PET/Al tape wrap</li> <li>• Shield-2: 0.10mm Alpha Conductor wire braid</li> <li>• Sheath: Flexible PVC (Green) approx. 8.0mm diameter (25 AWG)</li> <li>• Package: 50m/Reel</li> </ul>	
5	<p><b>FC-11-50</b> 1,425.-/ M.</p>	<p><b>Bulk Cables • Interconnect Coaxial Cable</b></p> <ul style="list-style-type: none"> <li>• Conductor: 37-strand <math>\alpha</math> (Alpha)- OCC Conductor 0.16mm diameter</li> <li>• Insulation: High-density polyethylene plus air-foam polyethylene 5.5mm diameter</li> <li>• Shield: 0.12mm braided <math>\alpha</math> (Alpha) Conductor</li> <li>• Sheath: Flexible PVC (Blue) approx. 8.0mm diameter (19 AWG)</li> <li>• Package: 50m/Ree</li> </ul>	

6	<p><b>μ-X Ag-50</b> 1,865.-/ M</p>	<p><b>Bulk Cables • Interconnect Coaxial Cable</b> <b>(Silver-Plated Wire with Teflon insulation)</b></p> <ul style="list-style-type: none"> <li>• Conductor: 37-strand Silver-Plated <b>α (Alpha)</b> μ-OFC Conductor • 0.16mm diameter</li> <li>• Insulation: Teflon plus air-foamed polyethylene 5.5mm diameter</li> <li>• Shield-1: PET/Al tape wrap</li> <li>• Shield-2: 0.12mm braided <b>α (Alpha)</b> conductor</li> <li>• Sheath: Flexible PVC (Light Blue) approx. 8.0mm diameter (19 AWG)</li> <li>• Package: 50m/Reel</li> </ul>	
7	<p><b>FC-61-100 (Red)</b> 265.-/M.</p> <p><b>FC-62-100 (Blue)</b> 265.-/M.</p> <p><b>FC-63-100 (Green)</b> 265.-/M.</p>	<p><b>Bulk Cables • Interconnect Coaxial Cable</b></p> <ul style="list-style-type: none"> <li>• Conductor: 19-strand <b>α (Alpha)</b> μ-OFC 0.2mm diameter</li> <li>• Insulation: High-density polyethylene plus air-foam polyethylene 3.4mm diameter</li> <li>• Shield-1: PET/Al tape wrap</li> <li>• Shield-2: 0.12mm braided <b>α (Alpha)</b> Conductor</li> <li>• Sheath: Flexible PVC (Red-61/Blue-62/Green-63), approx. 6.3mm diameter (19 AWG)</li> <li>• Package: 100m/Reel</li> </ul>	  
8	<p><b>μ- 2T-50</b> 1,245.-/M.</p>	<p><b>Bulk Cables • Speaker Cable</b></p> <ul style="list-style-type: none"> <li>• Conductor: 6 bundles 20 strands 0.18mm diameter <b>α (Alpha)</b> μ-OFC Conductor</li> <li>• Insulation: Polyethylene (Red/White) 5.1mm diameter</li> <li>• Sheath: Flexible PVC (Dark Green) approx. 13.5mm diameter (14 AWG)</li> <li>• Package: 50m/Reel</li> </ul>	
9	<p><b>FS-301-100</b> 440.-/ M.</p>	<p><b>Bulk Cables • Speaker Cable</b></p> <ul style="list-style-type: none"> <li>• Conductor: 7 bundles 34 strands 0.1mm diameter <b>α (Alpha)</b> μ-OFC Conductor</li> <li>• Insulation: Polyethylene (Red/White) 3mm diameter</li> <li>• Sheath: Flexible PVC (Pearl White) approx. 7.5mm diameter (14 AWG)</li> <li>• Package: 100m/Reel</li> </ul>	

10	<p><b>FS-303-100</b> 248.-/ M.</p>	<p><b>Bulk Cables • Speaker Cable</b></p> <ul style="list-style-type: none"> <li>• Conductor: 7 bundles 28 strands 0.1mm diameter <math>\alpha</math> (Alpha) <math>\mu</math>-OFC Conductor</li> <li>• Sheath: Flexible PVC (Pearl White) 4 x 8.4mm overall size (16 AWG)</li> <li>• Package: 10m/20m/30m per blister pack, 100m/Reel</li> </ul>	
11	<p><b>FS-502-50</b> 800.-/ M.</p>	<p><b>Bulk Cables • Speaker Cables</b></p> <ul style="list-style-type: none"> <li>• Conductor: 7 bundles 36 strands 0.1mm diameter <math>\alpha</math> (Alpha) <math>\mu</math>-OFC Conductor</li> <li>• Insulation: Polyethylene (Red/White) 3.0mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Shield: PET/Al tape wrap plus 7 strands 0.2mm <math>\alpha</math> (Alpha) conductor</li> <li>• Sheath: Flexible PVC (Pearl Light Blue) approx. 8mm diameter (14 AWG)</li> <li>• Package: 50m/Ree</li> </ul>	
12	<p><b><math>\mu</math>- 4.1T-50</b> 1,185.-/ M.</p>	<p><b>Bulk Cables • Speaker Cables • Bi-wire</b></p> <ul style="list-style-type: none"> <li>• Conductor-1: 21 strands 0.15mm plus 6 bundles 46 strands 0.1mm diameter <math>\alpha</math> (Alpha) <math>\mu</math>-OFC Conductor</li> <li>• Conductor-2: 7 bundles 5 strands 0.3mm diameter <math>\alpha</math> (Alpha) Conductor <math>\mu</math>-OFC</li> <li>• Insulation-1: Polypropylene (for high frequencies Blue/Black) 3.6mm diameter</li> <li>• Insulation-2: Polypropylene (for bass frequencies Red/White) 3.6mm diameter</li> <li>• Sheath: Flexible PVC (Dark Green) approx. 11.0mm diameter (13 AWG)</li> <li>• Package: 50m/Reel</li> </ul>	
13	<p><b>FS-15S-50</b> 2,480.-/ M.</p>	<p><b>Bulk Cables • Speaker Cables • Solid-Core</b></p> <ul style="list-style-type: none"> <li>• Conductor: 1.5mm diameter solid-core <math>\alpha</math> (Alpha) <math>\mu</math>-OFC Conductor</li> <li>• Insulation-1: Teflon (Clear) 2.2mm diameter</li> <li>• Insulation: Polyethylene (Red/White) 2.6mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Shield: PET/Al tape wrap plus 7 strands 0.2mm <math>\alpha</math> (Alpha) Conductor</li> <li>• Sheath: Flexible PVC (Dark Green) approx. 8.2mm diameter (15 AWG)</li> <li>• Package: 50m/Reel</li> </ul>	

14	<p><b>FS-<math>\alpha</math> (Alpha)-50</b> 5,695.-/ M.</p>	<p><b>Bulk Cables • Speaker Cables</b></p> <ul style="list-style-type: none"> <li>• Conductor: 6 bundles 20 strands 0.18mm diameter <math>\alpha</math> (Alpha) <math>\mu</math>- Conductor (PE into the center)</li> <li>• Insulation: Foamed Irradiated Polyethylene (Red/White) 5.1mm diameter</li> <li>• Cable Lay: Two cores twisted together</li> <li>• Sheath: Flexible PVC (Purple) approx. 13mm diameter (14 AWG)</li> <li>• Package: 50m/Ree</li> </ul>	
15	<p><b>FP-314Ag-50</b> 1,750.-/ M.</p>	<p><b>Bulk Cables • Power Cables</b></p> <ul style="list-style-type: none"> <li>• 37 strands silver-plated <math>\alpha</math> (Alpha) Conductor 0.25mm diameter <math>\times</math> 1 core plus 37 strands of 0.25mm diameter <math>\mu</math>-OFC <math>\alpha</math> (Alpha) Conductor <math>\times</math> 2 core</li> <li>• Insulation: Polyethylene (Red/White/Green) 3.4mm diameter</li> <li>• Inner Sheath: Flexible PVC (Black) 9.3mm diameter</li> <li>• Shield: 9 x 24 strands of 0.12mm braided <math>\alpha</math> (Alpha) conductor</li> <li>• Sheath: Flexible PVC (Brown) approx. 12.9mm diameter</li> </ul>	
16	<p><b>FP-3TS762-40</b> 4,150.-/ M.</p>	<p><b>Bulk Cables • Power Cables</b></p> <ul style="list-style-type: none"> <li>• Conductor: 7 bundles 35 strands <math>\cdot</math> 0.16mm diameter <math>\alpha</math> (Alpha) <math>\mu</math>-OFC</li> <li>• Insulation: Polyethylene (Red/Natural/Yellow) 5.2mm diameter</li> <li>• Inner Sheath: Flexible PVC (Black) 12.0mm diameter</li> <li>• Shield: 9 x 24 strands of 0.12mm stranded-braid <math>\alpha</math> (Alpha) conductor</li> <li>• Sheath: Flexible PVC (Dark Blue) approx. 15.5mm diameter.</li> </ul>	
17	<p><b>FP-<math>\alpha</math> (Alpha)3-40</b> 6,465.-/ M.</p>	<p><b>High Performance Power Cable • 1.8m</b></p> <ul style="list-style-type: none"> <li>• 56 inner and 29 outer strands <math>\cdot</math> 0.175mm diameter <math>\alpha</math> (Alpha) -OCC <math>\times</math> 3 core, 1.9mm diameter</li> <li>• Insulation: Polyethylene (Red/Natural/Yellow) 3.5mm diameter</li> <li>• Sheath (Inner): Flexible PVC (Black) 9.5mm diameter</li> <li>• Shield: 9 x 24 0.12mm copper wire stranded braid</li> <li>• Sheath (Outer): Flexible PVC (Dark Blue) 14.2mm diameter</li> </ul>	
18	<p><b>FP-3TS20-50</b> 3,915.-/ M.</p>	<p><b>Bulk Cables • Power Cables</b></p> <ul style="list-style-type: none"> <li>• Conductor: 56 inner and 29 outer strands 0.18mm diameter <math>\alpha</math> (Alpha) -OCC</li> <li>• Insulation: Polyethylene (Red/Natural/Yellow) 3.53mm diameter</li> <li>• Inner Sheath: Flexible PVC (Black) 9.6mm diameter</li> <li>• Shield: 9 x 24 strands of 0.12mm stranded-braid <math>\alpha</math> (Alpha) conductor</li> <li>• Sheath: Flexible PVC (Dark Blue) approx. 14.3mm diameter.</li> </ul>	