





## Finished Cable Products

|   |  |   |   |
|---|--|---|---|
| 1 | <p><b>Power Reference III</b><br/>69,040.-/pcs.</p>      | <p><b>High End Performance Power Cables • 1.8 m</b></p> <ul style="list-style-type: none"> <li>• 49-strand <math>\alpha</math> (Alpha) <math>\mu</math> - conductor 0.32mm x 3 cores, 2.5mm diameter</li> <li>• Insulation: Irradiated PE (Red/Natural/Yellow) 5mm diameter</li> <li>• Sheath: Two layers flexible PVC (Dark Green) 15mm diameter</li> <li>• Shield: Special EMI- and noise-absorbent <i>Formula GC-303 module</i></li> <li>• Jacket: Nylon yarn braid approx. 16.5mm diameter</li> <li>• Connectors: FI-25(R) IEC and FI-25M(R) Power Connector</li> </ul>   |    |
| 2 | <p><b>Audio Reference III (RCA)</b><br/>65,900.-/set</p> | <p><b>High End Performance Interconnect • 1.2 m</b></p> <ul style="list-style-type: none"> <li>• 30-strand <math>\alpha</math> (Alpha)-OCC Conductor 0.18mm , 1.14mm diameter</li> <li>• Insulation: 30% air-foamed HDPE (Red/White) 2.60mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Cable Wrap: Non-woven fabric wrap approx. 5.8mm diameter</li> <li>• Shield-1: 0.12mm braided <math>\alpha</math> (Alpha) Conductor braid density: 80% UP x 6.3mm diameter</li> <li>• Sheath: Two layers flexible PVC (Dark Brown) 8.0mm diameter</li> <li>• Shield-2: Special EMI- and noise-absorbent <i>Formula GC-303 module</i></li> <li>• Jacket: Nylon yarn braid approx. 10.5mm diameter.</li> <li>• Connectors: FP-106(R) RCA</li> </ul>                    |   |
| 3 | <p><b>Audio Reference III (XLR)</b><br/>75,320.-/set</p> | <p><b>High End Performance Interconnect • 1.2 m</b></p> <ul style="list-style-type: none"> <li>• 30-strand <math>\alpha</math> (Alpha)-OCC Conductor • 0.18mm, 1.14mm diameter</li> <li>• Insulation: 30% air-foamed HDPE (Red/White) 2.60mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Cable Wrap: Non-woven fabric wrap approx. 5.8mm diameter</li> <li>• Shield-1: 0.12mm braided <math>\alpha</math> (Alpha) Conductor braid density: 80% UP x 6.3mm diameter</li> <li>• Sheath: Two layers flexible PVC (Dark Brown) 8.0mm diameter</li> <li>• Shield-2: Special EMI- and noise-absorbent <i>Formula GC-303 module</i></li> <li>• Jacket: Nylon yarn braid approx. 10.5mm diameter.</li> <li>• Connectors: FP-601 M(R) and FP-602 F(R) XLR</li> </ul> |  |

|   |  |   |   |
|---|--|---|---|
| 4 | <p><b>Digital Reference III (RCA)</b><br/><i>47,075.-/pcs.</i></p>   | <p><b>High End Performance Digital Datalink • 1.2 m</b></p> <ul style="list-style-type: none"> <li>• 37-strand <math>\alpha</math> (Alpha)-OCC Conductor • 0.16mm, 1.15mm diameter</li> <li>• Insulation-1:HDPE 1.75mm diameter</li> <li>• Insulation-2: Air-formed PE, 5.5mm diameter</li> <li>• Shield-1: 0.12mm braided <math>\alpha</math> (Alpha) Conductor braid density: 80% UP x 6.3mm diameter</li> <li>• Sheath: Two layers flexible PVC (Aquamarine) 8mm diameter</li> <li>• Shield-2: Special fiberglass and copper wire stranded braid</li> <li>• Jacket: Nylon yarn braid approx. 10.5mm</li> <li>• Shield-3: Special EMI- and noise-absorbent <i>Formula GC-303 module</i></li> <li>• Connectors: FP-106(R) RCA or FP-3-117(R) BNC</li> </ul>  |    |
| 5 | <p><b>Digital Reference III (XLR)</b><br/><i>52,100.-/pcs.</i></p>   | <p><b>High End Performance Digital Datalink • 1.2m</b></p> <ul style="list-style-type: none"> <li>• 30-strand <math>\alpha</math> (Alpha)-OCC Conductor 0.18mm, 1.14mm diameter</li> <li>• Insulation: 30% air-foamed HDPE (Red/White) 2.60mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Cable Wrap: Non-woven fabric wrap approx. 5.8mm diameter</li> <li>• Shield-1: 0.12mm braided <math>\alpha</math> (Alpha) Conductor braid density: 80% UP x 6.3mm diameter</li> <li>• Sheath: Two layers flexible PVC (Dark Brown) 8.0mm diameter</li> <li>• Shield-2: Special fiberglass and copper wire stranded braid</li> <li>• Jacket: Nylon yarn braid approx. 10.5mm diameter.</li> <li>• Shield-3: Special EMI- and noise-absorbent <i>Formula GC-303 module</i></li> <li>• Connectors: FP-601 M(R) and FP-602 F(R) XLR</li> </ul> |   |
| 6 | <p><b>Speaker Reference III-04 • 2 meter</b><br/><i>75,320.-/set.</i></p> <p><b>Speaker Reference III-06 • 3 meter</b><br/><i>89,755.-/set</i></p> | <p><b>High End Performance Speaker Cable</b></p> <ul style="list-style-type: none"> <li>• 6 bundles of 20-strand <math>\alpha</math> (Alpha)-OCC Conductor 0.18mm, 2.7mm diameter</li> <li>• Insulation: Air-foamed Irradiated PE (Red/White) 5.1mm diameter</li> <li>• Cable Lay: Two cores twisted together</li> <li>• Sheath: Two layers flexible PVC (Purple/Red) 13mm diameter</li> <li>• Shield: Special EMI- and noise-absorbent <i>Formula GC-303 module</i></li> <li>• Jacket: Nylon yarn braid approx. 14.5mm</li> <li>• Connectors: FP-201(R) spade terminal or FP-202(R) Bananas</li> </ul>   |  |

**Remark : (G) = 24k Gold Plated, (R) = Rhodium Plated, (Ag) = Silver Plated, (Cu) = Non-Plated.**

*All metallic parts are treated with*

*FURUTECH Alpha Cryogenic and Demagnetizing Treatment*

FURUTECH reserves the right to change product specifications without prior notice.





**FURUTECH CO., LTD.**


[www.furutech.com](http://www.furutech.com)

[service@Furutech.com](mailto:service@Furutech.com)

*Make A More Powerful Connection with Furutech!*

## Finished Cable Products

|   |  |  |   |
|---|--|--|---|
| 1 | <p><b>Evolution Power</b></p> <p>31,380.-/pcs</p>          | <p><b>High Performance Audio Power Cable • 1.8 m</b></p> <ul style="list-style-type: none"> <li>• 7 bundles 35-strand <math>\alpha</math> (Alpha) <math>\mu</math>-OFC Conductor 0.18mm x 3 cores, 3.69mm diameter</li> <li>• Insulation: Polyethylene (Red/Natural/Yellow) 5.5mm diameter</li> <li>• Sheath (Inner): Flexible PVC (Black) 13.5mm diameter</li> <li>• Shield: 9 x 24-strand 0.12mm copper stranded wire braid</li> <li>• Sheath: Flexible PVC (Pearl Blue) Diameter: 17.5mm</li> <li>• Jacket: Nylon yarn braid approx. 18.5mm</li> <li>• Connectors FI-11(G) IEC Connector and FI-11M(G) Power Connector</li> </ul>                     |    |
| 2 | <p><b>Evolution Audio (RCA)</b></p> <p>30,755.-/set</p>    | <p><b>High Performance Audio Interconnects • 1.2 m</b></p> <ul style="list-style-type: none"> <li>• 80-strand <math>\alpha</math> (Alpha)-OCC Conductor 0.18mm, 1.86mm diameter</li> <li>• Insulation: Polypropylene (Red, White) 2.46mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Cable Wrap: Non-woven fabric wrap approx.5.0mm</li> <li>• Shield: 0.12mm braided <math>\alpha</math> (Alpha) Conductor 6.3mm diameter</li> <li>• Sheath: Flexible PVC (Dark Green) 9.0mm diameter</li> <li>• Jacket: Nylon yarn braid approx. 10mm</li> <li>• Connectors: FP-110(G) RCA</li> </ul>                        |   |
| 3 | <p><b>Evolution Audio (XLR)</b></p> <p>35,150.-/set</p>    | <p><b>High Performance Audio Interconnect • 1.2 m</b></p> <ul style="list-style-type: none"> <li>• 80-strand <math>\alpha</math> (Alpha)-OCC Conductor 0.18mm, 1.86mm diameter</li> <li>• Insulation: Polypropylene (Red/White) 2.46mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Cable Wrap: Non-woven fabric wrap approx. 5.0mm</li> <li>• Shield: 0.12mm braided <math>\alpha</math> (Alpha) Conductor approx. 6mm diameter</li> <li>• Sheath: Flexible PVC (Dark Green) 9.0mm diameter</li> <li>• Jacket: Nylon yarn braid approx. 10mm</li> <li>• Connectors: FP-701 M(G) and FP-702 F(G) XLR</li> </ul> |  |
| 4 | <p><b>Evolution Digital (RCA)</b></p> <p>18,200.-/pcs.</p> | <p><b>High Performance Digital Cable • 1.2 m</b></p> <ul style="list-style-type: none"> <li>• 37-strand <math>\alpha</math> (Alpha)-OCC Conductor • 0.16mm, 1.15mm diameter</li> <li>• Insulation-1: HDPE 1.75mm diameter</li> <li>• Insulation-2: Air-foamed PE 5.5mm diameter</li> <li>• Shield-2: 0.12mm braided <math>\alpha</math> (Alpha) Conductor ,6.3mm diameter</li> <li>• Jacket: Nylon yarn braid approx. 9.5mm</li> <li>• Connectors: FP-110(G) RCA or FP-3-117(R) BNC.</li> </ul>  |  |

|   |   |   |   |
|---|---|---|---|
| 5 | <p><b>Evolution Digital (XLR)</b><br/>21,970.-/pcs.</p>   | <p><b>High Performance Audio Digital Cable • 1.2 m</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) <math>\mu</math>-OFC Conductor 1.3mm diameter</li> <li>• Insulation: Polypropylene (White/Red) 2.4mm diameter</li> <li>• Shield: 0.12mm <math>\alpha</math> (Alpha) Conductor wire braid</li> <li>• Sheath: Two layers flexible PVC (Dark Green) 8mm diameter</li> <li>• Jacket: Nylon yarn braid approx. 9.5mm</li> <li>• Connectors: FP-701 M(G) and FP-702 F(G) XLR</li> </ul>                           |  |
| 6 | <p><b>Evolution Speaker-04 • 2 meter</b><br/>28,245.-/set</p> <p><b>Evolution Speaker-06 • 3 meter</b><br/>36,720.-/set</p> | <p><b>High Performance Audio Speaker Cable</b></p> <ul style="list-style-type: none"> <li>• 6 bundles 20-strand <math>\alpha</math> (Alpha) <math>\mu</math>-OFC Conductor 0.18mm, 2.81mm diameter</li> <li>• Insulation: Special polyethylene (Red/White) 5.1mm diameter</li> <li>• Cable Lay: Two cores twisted together with cotton yarn</li> <li>• Sheath: Two layers flexible PVC (Dark Green) 13.5mm diameter</li> <li>• Jacket: Nylon yarn braid approx. 14.5mm</li> <li>• Connectors FP-201(G) spade or FP-202(G) Banana</li> </ul> |  |

**Remark : (G) = 24k Gold Plated, (R) = Rhodium Plated, (Ag) = Silver Plated, (Cu) = Non-Plated.**

*All metallic parts are treated with*

*FURUTECH Alpha Cryogenic and Demagnetizing Treatment*

FURUTECH reserves the right to change product specifications without prior notice.

**FURUTECH CO., LTD.**

[www.furutech.com](http://www.furutech.com)

[service@Furutech.com](mailto:service@Furutech.com)

*Make A More Powerful Connection with Furutech!*