





Bulk and Finished Cable Products

1	<p>G 314Ag-18 8,785.-/pcs.</p>	<p>High Performance Power Cable • 1.8m</p> <ul style="list-style-type: none"> • 37 strands silver-plated α (Alpha) μ-OFC Conductor • 0.25mm diameter x 1 core plus 37 strands of 0.25mm diameter μ-OFC α (Alpha) Conductor x 2 core • Insulation: Polyethylene (Red/Natural/Yellow) 3.4mm diameter • Inner Sheath: Flexible PVC (Black) 9.3mm diameter • Shield: 9 x 24 strands of 0.12mm braided α (Alpha) conductor • Sheath: Flexible PVC (Brown) approx. 12.9mm diameter • Connectors: FI-15E(G) IEC and FI-15ME(G) power connector 	
2	<p>Absolute Power 17,575.-/pcs.</p>	<p>High Performance Power Cable • 1.8m</p> <ul style="list-style-type: none"> • 56 inner and 29 outer strands 0.175mm diameter α (Alpha) -OCC x 3 core, 1.9mm diameter • Insulation: Polyethylene (Red/Natural/Yellow) 3.5mm diameter • Sheath (Inner): Flexible PVC (Black) 9.5mm Diameter • Shield: 9 x 24 0.12mm copper wire stranded braid • Sheath (Outer): Flexible PVC (Dark Blue) 14.2mm diameter • Jacket: Nylon yarn braid approx. 15.5mm • Connectors: FI-15E(R) IEC and FI-15ME(R) 	
3	<p>G 20A-18 23,225.-/pcs.</p>	<p>High Performance 20A Power Cable • 1.8m</p> <ul style="list-style-type: none"> • 7 bundles 35-strand α (Alpha) μ-OFC conductor 0.16mm x 3 core, 3.5mm diameter • Insulation: Polyethylene (Red/Natural/Yellow) 5.2mm diameter • Sheath (Inner): Flexible PVC (Black) 12mm diameter • Shield: 9 x 24 0.12mm copper wire stranded braid • Sheath (Outer): Flexible PVC (Blue) 15.5mm diameter • Connectors: FI-31(G) IEC and FI-31M(G) power connector 	

4	<p>Evolution Power 20A/15A 25,040.-/pcs.</p>	<p>High Performance Power Cable • 1.8 m</p> <ul style="list-style-type: none"> • 7 bundles 35-strand α (Alpha) μ-OFC Conductor • 0.17mm x 3 cores, 3.55mm diameter • Insulation: Polyethylene (Red/Natural/Yellow) 5.25mm diameter • Inner Sheath: Flexible PVC (Black) 12mm diameter • Shield: 9 x 24-strand 0.12mm copper stranded braid • Sheath: Flexible PVC (Pearl Blue) 17.5mm diameter • Jacket: Nylon yarn braid approx. 16.5mm • Connectors: FI-11(G) IEC and FI-31M(G) Power Connector 	
5	<p>G-320Ag-18 6,200.-/pcs.</p>	<p>High Performance Power Cable • 1.8 m</p> <ul style="list-style-type: none"> • Red- 37 strands of 0.26mm silver-plated α (Alpha) OFC Conductor / Yellow -37 strands of 0.26mm silver-plated α (Alpha) OFC Conductor / Green- 37 strands of 0.26mm α (Alpha) OFC Conductor • Insulation: Polyethylene (Red/Natural/Yellow) 3.5mm diameter • Fillers: Cotton with paper tape wrap • Sheath: Flexible PVC (Burgundy) approx. 10mm diameter 	
6	<p>G-320Ag-18A Angle Connector 6,200.-/pcs.</p>	<p>High Performance Power Cable • 1.8 m</p> <ul style="list-style-type: none"> • Red- 37 strands of 0.26mm silver-plated α (Alpha) OFC Conductor / Yellow -37 strands of 0.26mm silver-plated α (Alpha) OFC Conductor / Green- 37 strands of 0.26mm α (Alpha) OFC Conductor • Insulation: Polyethylene (Red/Natural/Yellow) 3.5mm diameter • Fillers: Cotton with paper tape wrap • Sheath: Flexible PVC (Burgundy) approx. 10mm diameter 	
7	<p>G-320Ag-18F8 Figure 8 Connector 6,200.-/pcs.</p>	<p>High Performance Power Cable • 1.8 m</p> <ul style="list-style-type: none"> • Red- 37 strands of 0.26mm silver-plated α (Alpha) OFC Conductor / Yellow -37 strands of 0.26mm silver-plated α (Alpha) OFC Conductor / Green- 37 strands of 0.26mm α (Alpha) OFC Conductor • Insulation: Polyethylene (Red/Natural/Yellow) 3.5mm diameter • Fillers: Cotton with paper tape wrap • Sheath: Flexible PVC (Burgundy) approx. 10mm diameter 	

Remark : (G) = 24k Gold Plated, (R) = Rhodium Plated, (Ag) = Silver Plated, (Cu) = Non-Plated.

All metallic parts are treated with FURUTECH Alpha Cryogenic and Demagnetizing Treatment

FURUTECH reserves the right to change product specifications without prior notice.

FURUTECH CO., LTD.

www.furutech.com

service@Furutech.com

Make A More Powerful Connection with Furutech!