





Power Cables & Power Distributors: European and other product versions

1	<p>Power Ref. III (FI-E35)</p> <p>69,040.-/pcs.</p>	<p>Power Cord (1.8mx1)---Europe version</p> <ul style="list-style-type: none"> • 49-strand α (Alpha) μ-conductor • 0.32mm x 3 cores, 2.5mm diameter • Insulation: Irradiated PE (Red/Natural/Yellow) 5mm diameter • Sheath: Two layers flexible PVC (Dark Green) 15mm diameter • Shield: Special EMI- and noise-absorbent <i>Formula GC-303 module</i> • Jacket: Nylon yarn braid approx. 16.5mm diameter • Connectors: FI-25(R) IEC and FI-E35(R) SCHUKO Connector 	
2	<p>Evolution Power (FI-E11)</p> <p>31,380.-/pcs.</p>	<p>Power Cord (1.8mx1)---Europe version</p> <ul style="list-style-type: none"> • 7 bundles 35-strand α (Alpha) μ-OFC Conductor • 0.18mm x 3 cores, 3.69mm diameter • Insulation: Polyethylene (Red/Natural/Yellow) 5.5mm diameter • Sheath (Inner): Flexible PVC (Black) 13.5mm diameter • Shield: 9 x 24-strand 0.12mm copper stranded wire braid • Sheath: Flexible PVC (Pearl Blue) Diameter: 17.5mm • Jacket: Nylon yarn braid approx. 18.5mm • Connectors:FI-11(G) IEC Connector and FI-E11(G) SCHUKO Connector 	
3	<p>Power Ref. III (FI-UK)</p> <p>69,985.-/pcs.</p>	<p>Power Cord (1.8m x1) with FI-UK (R) Connector</p> <ul style="list-style-type: none"> • 49-strand α (Alpha) μ-conductor 0.32mm x 3 cores, 2.5mm diameter • Insulation: Irradiated PE (Red/Natural/Yellow) 5mm diameter • Sheath: Two layers flexible PVC (Dark Green) 15mm diameter • Shield: Special EMI- and noise-absorbent <i>Formula GC-303 module</i> • Jacket: Nylon yarn braid approx. 16.5mm diameter • Connectors: FI-25(R) IEC and FI-UK(R) Power Connector 	
4	<p>Evolution Power (FI-UK)</p> <p>34,200.-/pcs.</p>	<p>Power Cord (1.8m x1) with FI-UK (G) Connector</p> <ul style="list-style-type: none"> • 7 bundles 35-strand α (Alpha) μ-OFC Conductor 0.18mm x 3 cores, 3.69mm diameter • Insulation: Polyethylene (Red/Natural/Yellow) 5.5mm diameter • Sheath (Inner): Flexible PVC (Black) 13.5mm diameter • Shield: 9 x 24-strand 0.12mm copper stranded wire braid • Sheath: Flexible PVC (Pearl Blue) Diameter: 17.5mm • Jacket: Nylon yarn braid approx. 18.5mm • Connectors:FI-11(G) IEC Connector and FI-UK(G) Power Connector 	

5	<p>Power Ref. III (FI-AU) 69,040.-/pcs.</p>	<p>Power Cord (1.8m x1) with FI-AU3112(R) Connector</p> <ul style="list-style-type: none"> • 49-strand α (Alpha) μ - conductor • 0.32mm x 3 cores, 2.5mm diameter • Insulation: Irradiated PE (Red/Natural/Yellow) 5mm diameter • Sheath: Two layers flexible PVC (Dark Green) 15mm diameter • Shield: Special EMI- and noise-absorbent <i>Formula GC-303 module</i> • Jacket: Nylon yarn braid approx. 16.5mm diameter • Connectors: FI-25(R) IEC and FI-AU(R) Power Connector 	
6	<p>Evolution Power (FI-AU) 32,950.-/pcs.</p>	<p>Power Cord (1.8m x1) with FI-AU3112(G) Connector</p> <ul style="list-style-type: none"> • 7 bundles 35-strand α (Alpha) μ-OFC Conductor • 0.18mm x 3 cores, 3.69mm diameter • Insulation: Polyethylene (Red/Natural/Yellow) 5.5mm diameter • Sheath (Inner): Flexible PVC (Black) 13.5mm diameter • Shield: 9 x 24-strand 0.12mm copper stranded wire braid • Sheath: Flexible PVC (Pearl Blue) Diameter: 17.5mm • Jacket: Nylon yarn braid approx. 18.5mm • Connectors: FI-11(G) IEC Connector and FI-AU(G) Power Connector 	
7	<p>G 314Ag-18 (Schuko) 9,415.-/pcs.</p>	<p>High Performance Power Cable • 1.8m</p> <ul style="list-style-type: none"> • 37 strands silver-plated α (Alpha) μ-OFC Conductor • 0.25mm diameter x 1 core plus 37 strands of 0.25mm diameter μ-OFC α (Alpha) Conductor x 2 core • Insulation: Polyethylene (Red/Natural/Yellow) 3.4mm diameter • Inner Sheath: Flexible PVC (Black) 9.3mm diameter • Shield: 9 x 24 strands of 0.12mm braided α (Alpha) conductor • Sheath: Flexible PVC (Brown) approx. 12.9mm diameter • Connectors: FI-15E(G) IEC and FI- E 11 (G) power connector 	
8	<p>Absolute Power -18 (Schuko) 16,945.-/pcs.</p>	<p>High Performance Power Cable • 1.8m</p> <ul style="list-style-type: none"> • 56 inner and 29 outer strands 0.175mm diameter α (Alpha) -OCC x 3 core, 1.9mm diameter • Insulation: Polyethylene (Red/Natural/Yellow) 3.5mm diameter • Sheath (Inner): Flexible PVC (Black) 9.5mm Diameter • Shield: 9 x 24 0.12mm copper wire stranded braid • Sheath (Outer): Flexible PVC (Dark Blue) 14.2mm diameter • Jacket: Nylon yarn braid approx. 15.5mm • Connectors: FI-15E(R) IEC and FI-E11(G) 	

9	<p>e-TP609E (Europe version) 61,510.-/pcs.</p>	<p>AC Power Distributor (High End Performance)</p> <ul style="list-style-type: none"> • Features Axial Locking System • GC-303 EMI-Absorbent Internal Coating • Chassis CNC machined from solid aluminum and equipped with mounting spikes • Special Vibration Dampener Coating. • Outputs: 6 Outlets • Input: 10A/250V IEC Inlet • Dimensions: 246mm (W) x 130mm (D) x 56mm (H) • Rated: 10A/250V • Net Weight: 2.85Kgs 	
10	<p>RTP-6E (Europe version) 47,075.-/pcs.</p>	<p>AC Power Distributor (High End Performance)</p> <ul style="list-style-type: none"> • GC-303 EMI-Absorbent Internal Coating • Chassis CNC machined from solid aluminum • Outputs: 6 Outlets • Input: 10A/250V IEC Inlet • Dimensions: 230mm (W) x 110mm (D) x 56mm (H) • Rated: 10A/250V • Net Weight: 2.5Kgs 	
11	<p>e-TP60E (Europe version) 17,575.-/pcs.</p>	<p>AC Power Distributor + GC-303</p> <ul style="list-style-type: none"> • GC-303 EMI-Absorbent Internal Coating • Outputs: 6 Outlets • Input: 10A/250V IEC Inlet • Dimensions: 200mm (W) x 130mm (D) x 60mm (H) • Rated: 10A/250V • Net Weight: 0.94kg 	
12	<p>e-TP80E (Europe version) 30,755.-/pcs.</p>	<p>AC Power Filter + GC-303</p> <ul style="list-style-type: none"> • GC-303 EMI-Absorbent Internal Coating plus EMI noise filter • Outputs: 8 outlets (4 filtered 4 non-filtered) • Input: 10A /250V IEC Inlet • Overall Size: 400mm (W) x 130mm (D) x 60mm (H) • Rated:10A/25V • Net Weight: 1.72Kgs 	

Remark : (G) = 24k Gold Plated, (R) = Rhodium Plated, (Ag) = Silver Plated, (Cu) = Non-Plated.

All metallic parts are treated with

FURUTECH Alpha Cryogenic and Demagnetizing Treatment

FURUTECH reserves the right to change product specifications without prior notice.

FURUTECH CO., LTD.

www.furutech.com

service@Furutech.com

Make A More Powerful Connection with Furutech!