

# FURUTECH

## PHONE JACK

<p><b>CF-735SM(R)</b> <b>3,200.-/pcs</b></p>	<p>New CF-735SM(R) 3.5mm stereo connector Main conductor: One-piece Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Pure copper conductor Ground conductor: Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Copper Alloy Insulation: audio grade Nylon Glass Fiber Resin Housing: Nonmagnetic stainless and carbon fiber finished. Cable Clamp: Copper Alloy Specified for core insulation diameters up to 5.3mm Connections: Soldered Dimensions: Housing: 10.2<math>\mu</math>x 27.2mm overall length; Total overall length: 44.7 mm approx.</p>	
<p><b>F35(G)</b> <b>1,600.-</b> <b>F35(R)</b> <b>2,050.-</b></p>	<ul style="list-style-type: none"> <li>• The Furutech F 35 --- 6.3 stereo to 3.5 stereo Adaptor</li> <li>• Main conductor: RoHS Compliant Gold-plated <math>\alpha</math> (Alpha) phosphor bronze and copper alloy</li> <li>• Insulated: POM resin.</li> <li>• Housing Material: SUS 304.</li> <li>• Overall Size: 10.6mm<math>\varnothing</math> X 61.0mm (L) approx.</li> </ul>	
<p><b>F63-S(G)</b> <b>1,600.-</b> <b>F63-S(R)</b> <b>2,050.-</b></p>	<ul style="list-style-type: none"> <li>• The Furutech F 63-S --- 3.5 Stereo to 6.3 stereo Adaptor</li> <li>• Main conductors: RoHS Compliant Gold-plated <math>\alpha</math> (Alpha) phosphor bronze and copper alloy</li> <li>• Insulated: POM resin.</li> <li>• Housing Material: SUS 304.</li> <li>• Overall Size: 9.5mm<math>\varnothing</math> X 45.0mm (L) approx</li> </ul>	
<p><b>CF-35 (R)</b> <b>2,900.-/ pcs</b></p>	<p>It converts a 6.3mm standard plug to 3.5mm stereo mini plug.</p> <p>- conductor: RoHS Directive compliance rhodium plating <math>\alpha</math>- phosphor bronze and copper alloy and insulation: POM resin -Housing: nonmagnetic rhodium plating <math>\alpha</math>- copper alloy carbon fiber finish</p> <p>External Dimensions: 11.5mm<math>\mu</math>X 61.0mm full length</p>	
<p><b>CF-63-S (R)</b> <b>2,900.-/ pcs</b></p>	<p>A 3.5mm stereo mini-plug and converts it to a 6.3mm standard plug</p> <p>Conductor unit adopts phosphor bronze, material for the insulating selected carefully such POM resin. Housing unit may enhance the vibration-damping properties of a carbon fiber finish.</p> <p>- conductor: RoHS Directive compliance rhodium plating <math>\alpha</math>- phosphor bronze and copper alloy and insulation: POM resin -Housing: nonmagnetic rhodium plating <math>\alpha</math>- copper alloy carbon fiber finish</p> <p>External Dimensions: 9.6mm<math>\mu</math>X 45.0mm full length</p>	

# FURUTECH

## PHONE JACK

<p><b>FP-Mono-63(G) FP-Mono-63L(G)</b></p> <p><b>2,250.-/ pcs</b></p>	<p><b>FP-Mono-63(G) / FP-Mono-63L(G)</b></p> <p><b>FEATURES</b> Furutech's beautifully finished, beautiful sounding FP-Mono-63(G) connector is the result of meticulous engineering and careful audition of various suitable materials. The FP-Mono-63(G) features a one-piece construction <math>\alpha</math> (Alpha) Copper Alloy conductor with PBT insulation for minimal impedance and a stainless housing for superior damping.</p> <p><b>SPECIFICATIONS</b> -Main conductor: One-piece Gold-plated <math>\alpha</math> (Alpha) Copper Alloy main conductor. -Ground conductor: Gold-plated <math>\alpha</math> (Alpha) Copper Alloy conductor. -Insulation: PBT. -Housing: stainless. -Cable Clamp: Copper Alloy -Specified for core insulation diameters up to 8.0mm. -Connections: Soldered. Net Weight: 18.4g Approx. Dimensions: Housing: 12.2<math>\mu</math>x 37.5mm overall length approx. Total overall length: 70 mm approx.</p>	
<p><b>FP-703(G)</b></p> <p><b>1,150.-/ pcs</b></p>	<p><b>FP-703 ( G )</b> <b>High Performance Phone Jackets ( Mono )</b> Gold plated ( Mono )</p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Eutectic cast copper alloy center pin</li> <li>• Copper alloy rear housing with PBT and fiberglass insulation</li> <li>• Connections: Soldered</li> <li>• Zn-Mg Alloy Casting body housing</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>• Specified for cable diameters up to 8mm</li> </ul> <p>Dimensions: Housing---17.8<math>\pm</math> 0.1mm diameter X65.8mm <math>\pm</math> 0.1mm, 97.3mm<math>\pm</math> 0.1mm overall length</p>	
<p><b>FP-704(G)</b></p> <p><b>1,350.-/ pcs</b></p>	<p><b>FP-704 ( G )</b> <b>High Performance Phone Jackets ( Stereo )</b> 24k Gold-Plated ( Stereo )</p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Eutectic cast copper alloy center pin</li> <li>• Copper alloy rear housing with PBT and fiberglass insulation</li> <li>• Connections: Soldered</li> <li>• Zn-Mg Alloy Casting body housing</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>• Specified for cable diameters up to 8mm</li> </ul> <p>Dimensions: Housing---17.8<math>\pm</math> 0.1mm diameter X65.8mm <math>\pm</math> 0.1mm, 97.8mm<math>\pm</math> 0.1mm overall length</p>	

# FURUTECH

## PHONE JACK




<p><b>CF-763SM(R)</b></p> <p><b>4,200.-/pcs</b></p>	<p><b>CF-763R</b> <b>6.3mm Stereo Connector</b></p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor: Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Phosphor bronze conductor</li> <li>•Insulation with Teflon Resin</li> <li>•Housing: Nonmagnetic stainless and carbon fiber finished.</li> <li>•Cable Clamp: Copper Alloy.</li> <li>•Specified for wire outer diameters up to 8.0mm</li> <li>•Connections: Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <p>Housing: 14<math>\psi</math>x 37.25mm overall length Total overall length: 70.5 mm approx.</p>	
	<p><b>CF-H800R</b> <b>Headphone Connector for SENNHEISER HD800</b></p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor: Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Phosphor bronze conductor</li> <li>•Insulation with Nylon+Fiberglass15% Resin</li> <li>•Main Body: Nonmagnetic stainless and carbon fiber finished</li> <li>•End Ring: Nonmagnetic stainless.</li> <li>•Fixed Tube: Copper Alloy.</li> <li>•Connections: Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Specified for wire outer diameters up to 3.8mm</li> <li>•Dimensions: Main Body: 8.5<math>\psi</math>x 24.0mm overall length Total overall length: 31.0 mm approx.</li> </ul>	
<p><b>FT-2PS-F (R)</b></p> <p><b>3,150.-/set</b> <b>(2pcs./set)</b></p>	<p><b>FT-2PS</b> <b>Headphone 2 Pin Connector for SENNHEISER</b></p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor: Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Phosphor bronze conductor</li> <li>•Insulation body injected with Liquid Crystal Polymer Resin</li> <li>•Housing cover: Matte black finished Nylon/fiberglass with piezo ceramic resin.</li> <li>•Cable Clamp: Copper Alloy for best damping effect.</li> <li>•Connections: Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Specified for core insulation diameters up to 3.5mm</li> <li>•Dimensions: Housing: 12.0 x 7.5 x 22.5mm overall length Total overall length: 37.0 mm approx.</li> </ul>	
<p><b>FT-610mF (R)</b></p> <p><b>1,600.-/pcs</b></p>	<p><b>FT-610mF</b> <b>mini XLR Female Connector</b></p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor: Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Phosphor bronze conductor</li> <li>•Insulation with super heat resistant Polyphenylene Sulfide Resin for best soldering results</li> <li>•Housing: Nonmagnetic stainless Black finished.</li> <li>•Cable Clamp: Superior Damping Copper Alloy.</li> <li>•Connections: Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Specified for core insulation diameters up to 5.0mm</li> <li>•Dimensions: Housing: 10.6<math>\psi</math>x 18.5mm overall length Total overall length: 34.7 mm approx.</li> </ul>	

# FURUTECH

## PHONE JACK

<p><b>FT-763SM(G)</b></p> <p><b>3,000.-/pcs</b></p> <p><b>FT-763SM(R)</b></p> <p><b>3,350.-/pcs</b></p>	<p><b>FT-763R</b> <b>6.3mm stereo Connector</b></p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor: Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Phosphor bronze conductor</li> <li>•Insulation with Teflon Resin</li> <li>•Housing: Nonmagnetic stainless.</li> <li>•Cable Clamp: Copper Alloy.</li> <li>•Connections: Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Specified for wire outer diameters up to 8.0mm</li> <li>•Dimensions: Housing: 12.24<math>\psi</math>x 37.25mm overall length Total overall length: 70.5 mm approx.</li> </ul>	
<p><b>FT-735SM(G)</b></p> <p><b>2,000.-/pcs</b></p> <p><b>FT-735SM(R)</b></p> <p><b>2,200.-/pcs</b></p>	<p><b>FT-735R</b> <b>3.5mm stereo Connector</b></p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor: Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Phosphor bronze conductor</li> <li>•Insulation with Teflon Resin</li> <li>•Housing: Nonmagnetic stainless.</li> <li>•Cable Clamp: Copper Alloy.</li> <li>•Connections: Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Specified for core insulation diameters up to 5.0mm</li> <li>•Dimensions: Housing: 9.0<math>\psi</math>x 23.0mm overall length Total overall length: 41.3 mm approx.</li> </ul>	
	<p><b>FT-H800R</b> <b>Headphone Connector for SENNHEISER HD800</b></p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor: Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Phosphor bronze conductor</li> <li>•Insulation with Nylon+Fiberglass15% Resin</li> <li>•Main Body/End Ring: Nonmagnetic stainless.</li> <li>•Fixed Tube: Copper Alloy.</li> <li>•Connections: Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Specified for wire outer diameters up to 3.8mm</li> <li>•Dimensions: Main Body: 8.5<math>\psi</math>x 24.0mm overall length Total overall length: 31.0 mm approx.</li> </ul>	
<p><b>FT-608mF (R)</b></p> <p><b>1,600.-/pcs</b></p>	<p><b>FT-608mF</b> <b>mini XLR Female Connector</b></p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor: Nonmagnetic Rhodium-plated <math>\alpha</math> (Alpha) Phosphor bronze conductor</li> <li>•Insulation with super heat resistant Polyphenylene Sulfide Resin for best soldering results</li> <li>•Housing: Nonmagnetic stainless.</li> <li>•Cable Clamp: Superior Damping Copper Alloy.</li> <li>•Connections: Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Specified for core insulation diameters up to 5.0mm</li> <li>•Dimensions: Housing: 10.6<math>\psi</math>x 18.5mm overall length Total overall length: 34.7 mm approx.</li> </ul>	

PHONE JACK

<p><b>CF-7254-N1 (R)</b></p> <p><b>3,200.-/pcs</b></p>	<p><b>CF-7254(R)</b> High End Performance 2.5mm (TRRS) Connector</p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor : Hybrid pin constructed with rhodium plated alpha hybrid copper and SUS</li> <li>•Ground conductor: Nonmagnetic Rhodium-plated α (Alpha) Hybrid Copper</li> <li>•Insulation : special audio grade P.P. Resin</li> <li>•Housing : Nonmagnetic stainless steel and carbon fiber finished.</li> <li>•Cable Clamp : Copper Alloy</li> <li>•Connections : Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Specified for core insulation diameters up to 5.3mm</li> <li>•Dimensions : Housing : 10.2 ψx 27.2mm overall length; Total overall length: 41.7 mm approx</li> </ul>	
<p><b>FT-7254 (R)</b></p> <p><b>2,400.-/ pcs</b></p>	<p><b>FT-7254(R)</b> High Performance 2.5mm (TRRS) Connector</p> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>•Main conductor : Hybrid pin constructed with rhodium plated alpha hybrid copper and SUS</li> <li>•Ground conductor: Nonmagnetic Rhodium-plated α (Alpha) Hybrid Copper</li> <li>•Insulation : special audio grade P.P. Resin</li> <li>•Housing : Nonmagnetic stainless</li> <li>•Cable Clamp : Copper Alloy</li> <li>•Connections : Soldered</li> </ul> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Specified for core insulation diameters up to 5.0mm</li> <li>•Dimensions : Housing : 10.3 ψx 2 5.0mm overall length; Total overall length: 39.6 mm approx</li> </ul>	
<p><b>CF-7445 (R)</b></p> <p><b>4,600.-/pcs</b></p>	<p><b>CF-7445(R)</b> High End Performance 4.4mm (TRRRS) Connector</p> <p><b>FEATURES</b></p> <p>Premier Performance and Legendary Build Quality Furutech makes a wide variety of OEM parts known the world over for their quality construction and superb sound. Our engineers examine every part of the signal and power path no matter how small and optimize each and every connection.</p> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Main conductor: One-piece rhodium-plated α (Alpha) Copper alloy main conductor.</li> <li>•Ground conductor: Rhodium-plated α (Alpha) Copper alloy conductor.</li> <li>•Insulation: audio grade POM.</li> <li>•Housing: Stainless and carbon fiber finished.</li> <li>•Cable Clamp: Copper Alloy.</li> <li>•Specified for core insulation diameters up to 6.0mm.</li> <li>•Connections: Soldered (light sanding of the plating on the soldering contacts may be required before soldering)</li> <li>•Net Weight: 8.8g Approx. Dimensions: Housing: 11.2ψx 30.8mm overall length approx.</li> <li>•Total overall length: 50.3 mm approx.</li> </ul>	
<p><b>FT-7445 (R)</b></p> <p><b>3,350.-/pcs</b></p>	<p><b>FT-7445(R)</b> High End Performance 4.4mm (TRRRS) Connector</p> <p><b>FEATURES</b></p> <p>Premier Performance and Legendary Build Quality Furutech makes a wide variety of OEM parts known the world over for their quality construction and superb sound. Our engineers examine every part of the signal and power path no matter how small and optimize each and every connection.</p> <p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>•Main conductor: One-piece rhodium-plated α (Alpha) Copper alloy main conductor.</li> <li>•Ground conductor: Rhodium-plated α (Alpha) Copper alloy conductor.</li> <li>•Insulation: Audio grade POM.</li> <li>•Housing: Stainless.</li> <li>•Cable Clamp: Copper Alloy.</li> <li>•Specified for core insulation diameters up to 6.0mm.</li> <li>•Connections: Soldered (light sanding of the plating on the solder contacts may be required before soldering).</li> <li>•Net Weight: 11.8g Approx.</li> <li>•Dimensions: Housing: 11.2ψx 30.8mm overall length approx.</li> <li>•Total overall length: 50.3 mm approx.</li> </ul>	