

FURUTECH

IEC Connector

<p>FI-33(R) เลิกผลิต</p> <p>FI-33(G) 5,900.-/pcs.</p>	<p>High End Performance 20A IEC Inlet</p> <ul style="list-style-type: none"> • Pure copper α (Alpha) Conductor • Material: Nylon/fiberglass • Specified for wire diameters of 4mm (set screw) • Dimensions: 60.4mm (W) x 30.4mm (D) x 38.7mm (H) • Rated: 20A/125V and 16A/250V 	
<p>FI-09(R) เลิกผลิต</p> <p>FI-09(G) 4,800.-/pcs.</p>	<p>High End Performance IEC Inlet</p> <p>Pure copper α (Alpha) Conductor</p> <ul style="list-style-type: none"> • Materials: Nylon/fiberglass • Specifications: Accommodates wire diameters to 4mm (set-screw) • Dimensions: 60 (W) x 30mm (D) x 36.2mm (H) • Body length 40.0mm x 44mm diameter x 80mm overall length • Rated: 15A/250V 	
<p>AC-INLET (R) 1,070.-/pcs.</p> <p>AC-INLET(G) 800.-/pcs</p>	<p>High Performance IEC Inlet</p> <ul style="list-style-type: none"> • α (Alpha) copper alloy conductor • PBT and fiberglass housing • Dimensions: 44.0mm (W) x 28.6mm (D) x 33.0mm (H) • Rating: 10A/250V • Standard : IEC 320-1 C14 • Approvals : UL/CSA/VDE/DEMKO/SEMKO/NEMKO/FIMKO 	
<p>FI-03(R) 1,500.-/pcs.</p> <p>FI-03(G) 1,350.-/pcs.</p>	<p>High Performance IEC Inlet</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic (low temperature) cast copper alloy Conductor • PBT and fiberglass housing • Connections: Soldered • Dimensions: 50.9mm (W) x 24.1mm (D) x 28.8 (H) • Rated: 15A/125V 10A/250V 	
<p>FI-06(R) เลิกผลิต</p> <p>FI-06(G) 1,800.-/pcs.</p>	<p>FI-06(G) & FI-06(R)</p> <p>Gold or Rhodium plated α (Alpha) Conductors milled from solid Pure Copper</p> <p>Rated: 15A/250V</p> <ul style="list-style-type: none"> • Materials: Nylon/fiberglass • Specifications: Accommodates wire diameters up to 3.5mm (set-screw) • Dimensions: 50.5 (W) x 23.9mm (D) x 33.5mm (H) ± 0.1mm 	

FURUTECH

IEC Connector

 <p>FI-06 NCF(R) 2,600-/pcs.</p>	<p>Furutech's Ultimate IEC Inlet Series</p> <ul style="list-style-type: none"> • α (Alpha) Pure-Copper Rhodium-plated Conductor • Materials: Nylon/fiberglass with special "NCF" anti-resonance damping material - nano-sized crystalline, piezo ceramic particles and carbon powder • Specifications: Accommodates wire diameters up to 3.5mm (set-screw) • Dimensions: 50.5 (W) x 23.9mm (D) x 33.5mm (H) ±0.1mm • Rated: 15A/250V 	
 <p>FI-09 NCF 6,900-/pcs.</p>	<p>SPECIFICATIONS</p> <ul style="list-style-type: none"> • α (Alpha) Pure-Copper Rhodium-plated Conductor • Materials: Nylon/fiberglass with special "NCF" anti-resonance damping material - nano-sized crystalline, piezo ceramic particles and carbon powder • Specifications: Accommodates wire diameters up to 4.0mm (set-screw) • Dimensions: 60.5 (W) x 30.2mm (D) x 36.2mm (H) ±0.1mm • Type: 2-pole+earth, Rated: 15A/250V 	
 <p>FI-33 NCF 7,450-/pcs.</p>	<p>SPECIFICATIONS</p> <ul style="list-style-type: none"> • α (Alpha) Pure-Copper Rhodium-plated Conductor • Materials: Nylon/fiberglass with special "NCF" anti-resonance damping material - nano-sized crystalline, piezo ceramic particles and carbon powder • Specifications: Accommodates wire diameters up to 4.0mm (set-screw) • Dimensions: 60.5 (W) x 30.4mm (D) x 38.7mm (H) ±0.1mm • Type: 2-pole+earth, Rated: 16A/250V // 20A/125V 	